TREMproof 250GC

Table of Contents

TREMproof 250GC-R 5 GAL SDS 1

TREMproof 250GC-R-55 GAL 21

TREMproof 250GC-R-LV 5 GAL SDS 41

TREMproof 250GC-R-LV 55 GAL SDS 61

TREMproof 250GC-SL 5 GAL SDS 81

TREMproof 250GC-SL 55 GAL SDS 101

TREMproof 250GC-SL-LV 5 GAL SDS 121

TREMproof 250GC-SL-LV 55 GAL SDS 141

TREMproof 250GC-T 2 GAL SDS 161

TREMproof 250GC-T 5 GAL SDS 181

SAFETY DATA SHEET

1. Identification

Material name: TREMPROOF 250 GC-R 5 GAL PAIL
Material: 304510A 805

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 3

Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	21.16 %
Acute toxicity, dermal	27.34 %
Acute toxicity, inhalation, vapor	97.98 %
Acute toxicity, inhalation, dust or mist	52.68 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	87.26 %

Chronic hazards to the aquatic environment	98.19 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement:
Flammable liquid and vapor.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/…] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/… IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Wash contaminated clothing before reuse. In case of fire: Use… to extinguish.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Aromatic process oil	64741-62-4	20 - <50%
Petroleum distillates	64742-47-8	5 - <10%
Calcium Carbonate (Limestone)	1317-65-3	5 - <10%
Polyvinyl chloride	9002-86-2	5 - <10%
Carbon Black	1333-86-4	1 - <5%
Calcium oxide	1305-78-8	1 - <5%
Xylene	1330-20-7	0.1 - <1%
Isophorone Diisocyanate	4098-71-9	0.1 - <1%
Ethylbenzene	100-41-4	0.1 - <1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - <1%
Nonane	111-84-2	0.1 - <1%
1,2,4-Trimethylbenzene	95-63-6	0.1 - <1%
Iodopropynyl butylcarbamate	55406-53-6	0.01 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation: Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.

Skin Contact: Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment:	Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
Methods and material for containment and cleaning up:	Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
Notification Procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store locked up. Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air

				Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm	655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm	655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL		80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm	655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm	435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Nonane	TWA	200 ppm		US. ACGIH Threshold Limit Values (02 2012)
1,2,4-Trimethylbenzene	REL	25 ppm	125 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	TWA	25 ppm	125 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	25 ppm	125 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	AN ESL		25 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)

	ST ESL	140 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	ST ESL	700 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	AN ESL	125 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	TWA PEL	25 ppm 125 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	25 ppm	US. ACGIH Threshold Limit Values (2011)

Chemical name	Type	Exposure Limit Values	Source
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Petroleum distillates	TWA	525 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA		1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA		3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA		3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium oxide	TWA		2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA		2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA		2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm	0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational

			Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:

Use explosion-proof ventilation equipment. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection:

Use suitable protective gloves if risk of skin contact.

Other:

Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Dark brown
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	60 °C 140 °F(Setaflash Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.22
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous reactions: No data available.

Conditions to avoid: Heat, sparks, flames.

Incompatible Materials: Alcohols. Amines. Strong acids. Strong bases. Water, moisture.

Hazardous Decomposition Products: Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.

Skin Contact: May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.

Eye contact: Eye contact is possible and should be avoided.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral
Product: ATEmix: 9,576.9 mg/kg

Dermal
Product: ATEmix: 3,218.14 mg/kg

Inhalation
Product: ATEmix: 4.34 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Petroleum distillates	in vivo (Rabbit): Irritating Experimental result, Key study
Carbon Black	in vivo (Rabbit): Not irritant Experimental result, Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
Nonane	in vivo (Rabbit): Irritating Read-across based on grouping of substances (category approach), Key study
1,2,4-Trimethylbenzene	in vivo (Rabbit): Irritating Read-across from supporting substance (structural analogue or surrogate), Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Petroleum distillates	Rabbit, 24 - 72 hrs: Not irritating
Carbon Black	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating
Nonane	Rabbit, 24 - 72 hrs: Not irritating
1,2,4-Trimethylbenzene	Rabbit, 30 min: Not irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Aromatic process oil	Overall evaluation: Possibly carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Petroleum distillates	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 2.9 mg/l Mortality
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality
1,2,4-Trimethylbenzene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.19 - 8.28 mg/l Mortality
Iodopropynyl butylcarbamate	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 0.05 - 0.089 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Aromatic process oil	NOAEL (Oncorhynchus mykiss, 28 d): 0.1 mg/l QSAR QSAR, Key study
Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Specified substance(s):

Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Nonane	Log Kow: 5.46

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

UN1139, COATING SOLUTION, 3, PG III

Further Information:
The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity	OSHA hazard(s)
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system
Crystalline Silica (Quartz)/ Silica Sand	kidney effects lung effects immune system effects Cancer

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Nonane	100 lbs.
Chrysene	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

Chemical Identity	Reportable quantity	Threshold Planning Quantity
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Isophorone Diisocyanate	
Ethylbenzene	1000 lbs.
Nonane	100 lbs.
Chrysene	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Isophorone Diisocyanate	500lbs
Aromatic process oil	10000 lbs
Petroleum distillates	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Polyvinyl chloride	10000 lbs
Carbon Black	10000 lbs
Calcium oxide	10000 lbs
Xylene	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Nonane	10000 lbs
1,2,4-Trimethylbenzene	10000 lbs
Iodopropynyl butylcarbamate	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

Chemical Identity	Reportable quantity
Xylene	Reportable quantity: lbs.

US State Regulations

US. California Proposition 65



WARNING
Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Petroleum distillates
Calcium Carbonate (Limestone)
Polyvinyl chloride
Carbon Black
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List

Chemical Identity
Petroleum distillates
Calcium Carbonate (Limestone)
Carbon Black
Isophorone Diisocyanate
Chrysene
Benzo(a)pyrene
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Petroleum distillates
Calcium Carbonate (Limestone)
Carbon Black
Calcium oxide

US. Rhode Island RTK

Chemical Identity
Petroleum distillates
Calcium Carbonate (Limestone)
Polyvinyl chloride
Carbon Black

International regulations

Montreal protocol
Not applicable

Stockholm convention
Not applicable

Rotterdam convention
Not applicable

Kyoto protocol
Not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	179 g/l
VOC Method 310	:	14.69 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	07/21/2018
Version #:	1.1
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: TREMPROOF 250 GC-R-55 GAL
Material: 304510A 855

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 3

Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	21.16 %
Acute toxicity, dermal	27.34 %
Acute toxicity, inhalation, vapor	97.98 %
Acute toxicity, inhalation, dust or mist	52.68 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	87.26 %

Chronic hazards to the aquatic environment	98.19 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement:
Flammable liquid and vapor.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/…] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/… IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Wash contaminated clothing before reuse. In case of fire: Use… to extinguish.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Aromatic process oil	64741-62-4	20 - <50%
Petroleum distillates	64742-47-8	5 - <10%
Calcium Carbonate (Limestone)	1317-65-3	5 - <10%
Polyvinyl chloride	9002-86-2	5 - <10%
Carbon Black	1333-86-4	1 - <5%
Calcium oxide	1305-78-8	1 - <5%
Xylene	1330-20-7	0.1 - <1%
Isophorone Diisocyanate	4098-71-9	0.1 - <1%
Ethylbenzene	100-41-4	0.1 - <1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - <1%
Nonane	111-84-2	0.1 - <1%
1,2,4-Trimethylbenzene	95-63-6	0.1 - <1%
Iodopropynyl butylcarbamate	55406-53-6	0.01 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation: Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.

Skin Contact: Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment:	Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
Methods and material for containment and cleaning up:	Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
Notification Procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store locked up. Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air

				Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm	655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm	655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL		80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm	655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm	435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Nonane	TWA	200 ppm		US. ACGIH Threshold Limit Values (02 2012)
1,2,4-Trimethylbenzene	REL	25 ppm	125 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	TWA	25 ppm	125 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	25 ppm	125 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	AN ESL		25 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)

	ST ESL	140 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	ST ESL	700 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	AN ESL	125 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	TWA PEL	25 ppm 125 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	25 ppm	US. ACGIH Threshold Limit Values (2011)

Chemical name	Type	Exposure Limit Values	Source
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Petroleum distillates	TWA	525 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA		1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA		3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA		3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium oxide	TWA		2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA		2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA		2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm	0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational

			Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:

Use explosion-proof ventilation equipment. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection:

Use suitable protective gloves if risk of skin contact.

Other:

Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Dark brown
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	60 °C 140 °F(Setaflash Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.22
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous reactions: No data available.

Conditions to avoid: Heat, sparks, flames.

Incompatible Materials: Alcohols. Amines. Strong acids. Strong bases. Water, moisture.

Hazardous Decomposition Products: Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.

Skin Contact: May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.

Eye contact: Eye contact is possible and should be avoided.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral
Product: ATEmix: 9,576.9 mg/kg

Dermal
Product: ATEmix: 3,218.14 mg/kg

Inhalation
Product: ATEmix: 4.34 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Petroleum distillates	in vivo (Rabbit): Irritating Experimental result, Key study
Carbon Black	in vivo (Rabbit): Not irritant Experimental result, Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
Nonane	in vivo (Rabbit): Irritating Read-across based on grouping of substances (category approach), Key study
1,2,4-Trimethylbenzene	in vivo (Rabbit): Irritating Read-across from supporting substance (structural analogue or surrogate), Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Petroleum distillates	Rabbit, 24 - 72 hrs: Not irritating
Carbon Black	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating
Nonane	Rabbit, 24 - 72 hrs: Not irritating
1,2,4-Trimethylbenzene	Rabbit, 30 min: Not irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Aromatic process oil	Overall evaluation: Possibly carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Petroleum distillates	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 2.9 mg/l Mortality
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality
1,2,4-Trimethylbenzene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.19 - 8.28 mg/l Mortality
Iodopropynyl butylcarbamate	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 0.05 - 0.089 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Aromatic process oil	NOAEL (Oncorhynchus mykiss, 28 d): 0.1 mg/l QSAR QSAR, Key study
Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Specified substance(s):

Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Nonane	Log Kow: 5.46

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

UN1139, COATING SOLUTION, 3, PG III

Further Information:
The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity	OSHA hazard(s)
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system
Crystalline Silica (Quartz)/ Silica Sand	kidney effects lung effects immune system effects Cancer

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Nonane	100 lbs.
Chrysene	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

Chemical Identity	Reportable quantity	Threshold Planning Quantity
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Isophorone Diisocyanate	
Ethylbenzene	1000 lbs.
Nonane	100 lbs.
Chrysene	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Isophorone Diisocyanate	500lbs
Aromatic process oil	10000 lbs
Petroleum distillates	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Polyvinyl chloride	10000 lbs
Carbon Black	10000 lbs
Calcium oxide	10000 lbs
Xylene	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Nonane	10000 lbs
1,2,4-Trimethylbenzene	10000 lbs
Iodopropynyl butylcarbamate	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

Chemical Identity	Reportable quantity
Xylene	Reportable quantity: lbs.

US State Regulations

US. California Proposition 65



WARNING
Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Petroleum distillates
Calcium Carbonate (Limestone)
Polyvinyl chloride
Carbon Black
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List

Chemical Identity
Petroleum distillates
Calcium Carbonate (Limestone)
Carbon Black
Isophorone Diisocyanate
Chrysene
Benzo(a)pyrene
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Petroleum distillates
Calcium Carbonate (Limestone)
Carbon Black
Calcium oxide

US. Rhode Island RTK

Chemical Identity
Petroleum distillates
Calcium Carbonate (Limestone)
Polyvinyl chloride
Carbon Black

International regulations

Montreal protocol
Not applicable

Stockholm convention
Not applicable

Rotterdam convention
Not applicable

Kyoto protocol
Not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	179 g/l
VOC Method 310	:	14.69 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	07/21/2018
Version #:	1.1
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: TREMPROOF 250 GC-R-LV 5 GAL
Material: 304510LVA 805

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 4

Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A
Aspiration Hazard	Category 1

Unknown toxicity - Health

Acute toxicity, oral	20.9 %
Acute toxicity, dermal	34.82 %
Acute toxicity, inhalation, vapor	99.93 %
Acute toxicity, inhalation, dust or mist	61.64 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	95.66 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement:
Combustible liquid.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
May be fatal if swallowed and enters airways.
Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Wash contaminated clothing before reuse. In case of fire: Use… to extinguish.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Aromatic process oil	64741-62-4	30 - 60%
Calcium Carbonate (Limestone)	1317-65-3	7 - 13%
Polyvinyl chloride	9002-86-2	5 - 10%
Carbon Black	1333-86-4	3 - 7%
Petroleum distillates	64742-47-8	3 - 7%
Calcium oxide	1305-78-8	1 - 5%
Xylene	1330-20-7	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Ethylbenzene	100-41-4	0.1 - 1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Inhalation: Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.

Skin Contact: If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store locked up. Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)

	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm	655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL		80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm	655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm	435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	**Type**	**Exposure Limit Values**	**Source**
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Petroleum distillates	TWA	525 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work

				Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm	0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:	Use personal protective equipment as required.
Eye/face protection:	Wear goggles/face shield.
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Dark brown
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	66 °C 150 °F(Setaflash Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.09
Solubility(ies)	

Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	< 20.5 mm2/s (40 °C 104 °F)

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Alcohols. Amines. Strong acids. Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:	ATEmix: 19,841.97 mg/kg

Dermal
Product: ATEmix: 7,529.63 mg/kg

Inhalation
Product: ATEmix: 3.93 mg/l

Repeated dose toxicity
Product: No data available.

Skin Corrosion/Irritation
Product: No data available.

Specified substance(s):

Carbon Black	in vivo (Rabbit): Not irritant Experimental result, Key study
Petroleum distillates	in vivo (Rabbit): Irritating Experimental result, Key study
Calcium oxide	in vivo (Rabbit): Irritating Read-across from supporting substance (structural analogue or surrogate), Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study

Serious Eye Damage/Eye Irritation
Product: No data available.
Specified substance(s):

Carbon Black	Rabbit, 24 - 72 hrs: Not irritating
Petroleum distillates	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating

Respiratory or Skin Sensitization
Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause sensitization by inhalation.

Carcinogenicity
Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Aromatic process oil	Overall evaluation: Possibly carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:	No data available.

Specified substance(s):

Petroleum distillates	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 2.9 mg/l Mortality
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality

Aquatic Invertebrates

Product:	No data available.

Specified substance(s):

Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product:	No data available.

Specified substance(s):

Aromatic process oil	NOAEL (Oncorhynchus mykiss, 28 d): 0.1 mg/l QSAR QSAR, Key study
Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product:	No data available.

Toxicity to Aquatic Plants

Product:	No data available.

Persistence and Degradability

Biodegradation

Product:	No data available.

BOD/COD Ratio

Product:	No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chemical Identity	Reportable quantity
P-chlorobenzotrifluoride	De minimis concentration: TSCA 4% One-Time Export Notification only.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity	OSHA hazard(s)
Polyvinyl chloride	Blood
	Liver
	Cancer
	Flammability
	Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Chrysene	100 lbs.
Nonane	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

Chemical Identity	Reportable quantity	Threshold Planning Quantity
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Isophorone Diisocyanate	
Ethylbenzene	1000 lbs.
Chrysene	100 lbs.
Nonane	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Isophorone Diisocyanate	500lbs
Aromatic process oil	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Polyvinyl chloride	10000 lbs
Carbon Black	10000 lbs
Petroleum distillates	10000 lbs
Calcium oxide	10000 lbs
Xylene	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)
None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)
None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING
Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Calcium Carbonate (Limestone)
P-chlorobenzotrifluoride
Polyvinyl chloride
Carbon Black
Petroleum distillates
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List

Chemical Identity
Calcium Carbonate (Limestone)
Carbon Black
Petroleum distillates
Calcium oxide
Isophorone Diisocyanate
Chrysene
Benzo(a)pyrene
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Calcium Carbonate (Limestone)
Carbon Black
Petroleum distillates
Calcium oxide

US. Rhode Island RTK

Chemical Identity
Calcium Carbonate (Limestone)
Polyvinyl chloride
Carbon Black
Petroleum distillates
Calcium oxide

International regulations

Montreal protocol
Not applicable

Stockholm convention
Not applicable

Rotterdam convention
Not applicable

Kyoto protocol
Not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	91 g/l
VOC Method 310	:	7.86 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	07/21/2018
Version #:	1.1
Further Information:	No data available.

Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: TREMPROOF 250 GC-R-LV 55 GAL - ASEP
Material: 304510LVA 855

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information
Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 4

Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A
Aspiration Hazard	Category 1

Unknown toxicity - Health

Acute toxicity, oral	20.9 %
Acute toxicity, dermal	34.82 %
Acute toxicity, inhalation, vapor	99.93 %
Acute toxicity, inhalation, dust or mist	61.64 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	95.66 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement:
Combustible liquid.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
May be fatal if swallowed and enters airways.
Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Wash contaminated clothing before reuse. In case of fire: Use… to extinguish.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Aromatic process oil	64741-62-4	30 - 60%
Calcium Carbonate (Limestone)	1317-65-3	7 - 13%
Polyvinyl chloride	9002-86-2	5 - 10%
Carbon Black	1333-86-4	3 - 7%
Petroleum distillates	64742-47-8	3 - 7%
Calcium oxide	1305-78-8	1 - 5%
Xylene	1330-20-7	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Ethylbenzene	100-41-4	0.1 - 1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Inhalation: Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.

Skin Contact: If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store locked up. Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)

	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm	655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL		80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm	655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm	435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	**Type**	**Exposure Limit Values**	**Source**
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Petroleum distillates	TWA	525 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work

				Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm	0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:	Use personal protective equipment as required.
Eye/face protection:	Wear goggles/face shield.
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Dark brown
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	66 °C 150 °F(Setaflash Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.09
Solubility(ies)	

Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	< 20.5 mm2/s (40 °C 104 °F)

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Alcohols. Amines. Strong acids. Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:	ATEmix: 19,841.97 mg/kg

Dermal
Product: ATEmix: 7,529.63 mg/kg

Inhalation
Product: ATEmix: 3.93 mg/l

Repeated dose toxicity
Product: No data available.

Skin Corrosion/Irritation
Product: No data available.

Specified substance(s):

Carbon Black	in vivo (Rabbit): Not irritant Experimental result, Key study
Petroleum distillates	in vivo (Rabbit): Irritating Experimental result, Key study
Calcium oxide	in vivo (Rabbit): Irritating Read-across from supporting substance (structural analogue or surrogate), Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study

Serious Eye Damage/Eye Irritation
Product: No data available.
Specified substance(s):

Carbon Black	Rabbit, 24 - 72 hrs: Not irritating
Petroleum distillates	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating

Respiratory or Skin Sensitization
Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause sensitization by inhalation.

Carcinogenicity
Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Aromatic process oil	Overall evaluation: Possibly carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:	No data available.

Specified substance(s):

Petroleum distillates	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 2.9 mg/l Mortality
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality

Aquatic Invertebrates

Product:	No data available.

Specified substance(s):

Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product:	No data available.

Specified substance(s):

Aromatic process oil	NOAEL (Oncorhynchus mykiss, 28 d): 0.1 mg/l QSAR QSAR, Key study
Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product:	No data available.

Toxicity to Aquatic Plants

Product:	No data available.

Persistence and Degradability

Biodegradation

Product:	No data available.

BOD/COD Ratio

Product:	No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chemical Identity	Reportable quantity
P-chlorobenzotrifluoride	De minimis concentration: TSCA 4% One-Time Export Notification only.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity	OSHA hazard(s)
Polyvinyl chloride	Blood
	Liver
	Cancer
	Flammability
	Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Chrysene	100 lbs.
Nonane	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

Chemical Identity	Reportable quantity	Threshold Planning Quantity
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Isophorone Diisocyanate	
Ethylbenzene	1000 lbs.
Chrysene	100 lbs.
Nonane	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Isophorone Diisocyanate	500lbs
Aromatic process oil	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Polyvinyl chloride	10000 lbs
Carbon Black	10000 lbs
Petroleum distillates	10000 lbs
Calcium oxide	10000 lbs
Xylene	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)
None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)
None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING
Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Calcium Carbonate (Limestone)
P-chlorobenzotrifluoride
Polyvinyl chloride
Carbon Black
Petroleum distillates
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List

Chemical Identity
Calcium Carbonate (Limestone)
Carbon Black
Petroleum distillates
Calcium oxide
Isophorone Diisocyanate
Chrysene
Benzo(a)pyrene
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Calcium Carbonate (Limestone)
Carbon Black
Petroleum distillates
Calcium oxide

US. Rhode Island RTK

Chemical Identity
Calcium Carbonate (Limestone)
Polyvinyl chloride
Carbon Black
Petroleum distillates
Calcium oxide

International regulations

Montreal protocol
Not applicable

Stockholm convention
Not applicable

Rotterdam convention
Not applicable

Kyoto protocol
Not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	91 g/l
VOC Method 310	:	7.86 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	07/21/2018
Version #:	1.1
Further Information:	No data available.

Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: TREMPROOF 250 GC SL - 5 GAL
Material: 304511A 805

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 3

Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	23.55 %
Acute toxicity, dermal	28.08 %
Acute toxicity, inhalation, vapor	97.99 %
Acute toxicity, inhalation, dust or mist	53.77 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	88.93 %

Chronic hazards to the aquatic environment	98.16 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement:
Flammable liquid and vapor.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/…] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/… IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Wash contaminated clothing before reuse. In case of fire: Use… to extinguish.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Aromatic process oil	64741-62-4	20 - <50%
Calcium Carbonate (Limestone)	1317-65-3	10 - <20%
Petroleum distillates	64742-47-8	5 - <10%
Polyvinyl chloride	9002-86-2	5 - <10%
Calcium oxide	1305-78-8	1 - <5%
Carbon Black	1333-86-4	1 - <5%
Xylene	1330-20-7	1 - <5%
Isophorone Diisocyanate	4098-71-9	0.1 - <1%
Ethylbenzene	100-41-4	0.1 - <1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - <1%
Nonane	111-84-2	0.1 - <1%
Iodopropynyl butylcarbamate	55406-53-6	0.01 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation: Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.

Skin Contact: Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store locked up. Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air

				Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm	655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm	655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL		80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm	655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm	435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Nonane	TWA	200 ppm		US. ACGIH Threshold Limit Values (02 2012)

Chemical name	**Type**	**Exposure Limit Values**	**Source**
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational

			Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Petroleum distillates	TWA	525 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Xylene	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm	0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls	Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:	Use explosion-proof ventilation equipment. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Dark brown
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	60 °C 140 °F(Setaflash Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.22
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Alcohols. Amines. Strong acids. Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral
Product: ATEmix: 8,834.56 mg/kg

Dermal
Product: ATEmix: 3,266.9 mg/kg

Inhalation
Product: ATEmix: 4.34 mg/l

Repeated dose toxicity
Product: No data available.

Skin Corrosion/Irritation
Product: No data available.

Specified substance(s):

Petroleum distillates	in vivo (Rabbit): Irritating Experimental result, Key study
Carbon Black	in vivo (Rabbit): Not irritant Experimental result, Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
Nonane	in vivo (Rabbit): Irritating Read-across based on grouping of substances (category approach), Key study

Serious Eye Damage/Eye Irritation
Product: No data available.
Specified substance(s):

Petroleum distillates	Rabbit, 24 - 72 hrs: Not irritating
Carbon Black	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating

Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating
Nonane	Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Aromatic process oil	Overall evaluation: Possibly carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):

Petroleum distillates	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 2.9 mg/l Mortality
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality
Iodopropynyl butylcarbamate	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 0.05 - 0.089 mg/l Mortality

Aquatic Invertebrates
Product: No data available.

Specified substance(s):

Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):

Aromatic process oil	NOAEL (Oncorhynchus mykiss, 28 d): 0.1 mg/l QSAR QSAR, Key study
Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Specified substance(s):

Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Nonane	Log Kow: 5.46

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

UN1139, COATING SOLUTION, 3, PG III

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity	OSHA hazard(s)
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system
Crystalline Silica (Quartz)/ Silica Sand	kidney effects lung effects immune system effects Cancer

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Nonane	100 lbs.
Chrysene	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

Chemical Identity	Reportable quantity	Threshold Planning Quantity
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Isophorone Diisocyanate	
Ethylbenzene	1000 lbs.
Nonane	100 lbs.
Chrysene	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Isophorone Diisocyanate	500lbs
Aromatic process oil	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Petroleum distillates	10000 lbs
Polyvinyl chloride	10000 lbs
Calcium oxide	10000 lbs
Carbon Black	10000 lbs
Xylene	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Nonane	10000 lbs
Iodopropynyl butylcarbamate	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Xylene
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

Chemical Identity	Reportable quantity
Xylene	Reportable quantity: lbs.

US State Regulations

US. California Proposition 65



WARNING
Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Calcium Carbonate (Limestone)
Petroleum distillates
Polyvinyl chloride
Calcium oxide
Carbon Black
Xylene
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List

Chemical Identity
Calcium Carbonate (Limestone)
Petroleum distillates
Carbon Black
Xylene
Isophorone Diisocyanate
Chrysene
Benzo(a)pyrene
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Calcium Carbonate (Limestone)
Petroleum distillates
Calcium oxide
Carbon Black
Xylene

US. Rhode Island RTK

Chemical Identity
Calcium Carbonate (Limestone)
Petroleum distillates
Polyvinyl chloride
Carbon Black
Xylene

International regulations

Montreal protocol
Not applicable

Stockholm convention
Not applicable

Rotterdam convention
Not applicable

Kyoto protocol
Not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	159 g/l
VOC Method 310	:	13.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	07/21/2018
Version #:	1.1
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: TREMPROOF 250 GC-SL-55 GAL
Material: 304511A 855

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 3

Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	23.55 %
Acute toxicity, dermal	28.08 %
Acute toxicity, inhalation, vapor	97.99 %
Acute toxicity, inhalation, dust or mist	53.77 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	88.93 %

Chronic hazards to the aquatic environment	98.16 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement:
Flammable liquid and vapor.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/…] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/… IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Wash contaminated clothing before reuse. In case of fire: Use… to extinguish.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Aromatic process oil	64741-62-4	20 - <50%
Calcium Carbonate (Limestone)	1317-65-3	10 - <20%
Petroleum distillates	64742-47-8	5 - <10%
Polyvinyl chloride	9002-86-2	5 - <10%
Calcium oxide	1305-78-8	1 - <5%
Carbon Black	1333-86-4	1 - <5%
Xylene	1330-20-7	1 - <5%
Isophorone Diisocyanate	4098-71-9	0.1 - <1%
Ethylbenzene	100-41-4	0.1 - <1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - <1%
Nonane	111-84-2	0.1 - <1%
Iodopropynyl butylcarbamate	55406-53-6	0.01 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation: Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.

Skin Contact: Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store locked up. Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air

				Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm	655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm	655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL		80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm	655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm	435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Nonane	TWA	200 ppm		US. ACGIH Threshold Limit Values (02 2012)

Chemical name	**Type**	**Exposure Limit Values**	**Source**
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational

			Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Petroleum distillates	TWA	525 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Xylene	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm	0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls	Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:	Use explosion-proof ventilation equipment. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Dark brown
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	60 °C 140 °F(Setaflash Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.22
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Alcohols. Amines. Strong acids. Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral
Product: ATEmix: 8,834.56 mg/kg

Dermal
Product: ATEmix: 3,266.9 mg/kg

Inhalation
Product: ATEmix: 4.34 mg/l

Repeated dose toxicity
Product: No data available.

Skin Corrosion/Irritation
Product: No data available.

Specified substance(s):

Petroleum distillates	in vivo (Rabbit): Irritating Experimental result, Key study
Carbon Black	in vivo (Rabbit): Not irritant Experimental result, Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
Nonane	in vivo (Rabbit): Irritating Read-across based on grouping of substances (category approach), Key study

Serious Eye Damage/Eye Irritation
Product: No data available.
Specified substance(s):

Petroleum distillates	Rabbit, 24 - 72 hrs: Not irritating
Carbon Black	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating

Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating
Nonane	Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Aromatic process oil	Overall evaluation: Possibly carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):

Petroleum distillates	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 2.9 mg/l Mortality
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality
Iodopropynyl butylcarbamate	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 0.05 - 0.089 mg/l Mortality

Aquatic Invertebrates
Product: No data available.

Specified substance(s):

Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):

Aromatic process oil	NOAEL (Oncorhynchus mykiss, 28 d): 0.1 mg/l QSAR QSAR, Key study
Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Specified substance(s):

Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Nonane	Log Kow: 5.46

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

UN1139, COATING SOLUTION, 3, PG III

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity	OSHA hazard(s)
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system
Crystalline Silica (Quartz)/ Silica Sand	kidney effects lung effects immune system effects Cancer

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Nonane	100 lbs.
Chrysene	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

Chemical Identity	Reportable quantity	Threshold Planning Quantity
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Isophorone Diisocyanate	
Ethylbenzene	1000 lbs.
Nonane	100 lbs.
Chrysene	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Isophorone Diisocyanate	500lbs
Aromatic process oil	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Petroleum distillates	10000 lbs
Polyvinyl chloride	10000 lbs
Calcium oxide	10000 lbs
Carbon Black	10000 lbs
Xylene	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Nonane	10000 lbs
Iodopropynyl butylcarbamate	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Xylene
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

Chemical Identity	Reportable quantity
Xylene	Reportable quantity: lbs.

US State Regulations

US. California Proposition 65



WARNING
Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Calcium Carbonate (Limestone)
Petroleum distillates
Polyvinyl chloride
Calcium oxide
Carbon Black
Xylene
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List

Chemical Identity
Calcium Carbonate (Limestone)
Petroleum distillates
Carbon Black
Xylene
Isophorone Diisocyanate
Chrysene
Benzo(a)pyrene
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Calcium Carbonate (Limestone)
Petroleum distillates
Calcium oxide
Carbon Black
Xylene

US. Rhode Island RTK

Chemical Identity
Calcium Carbonate (Limestone)
Petroleum distillates
Polyvinyl chloride
Carbon Black
Xylene

International regulations

Montreal protocol
Not applicable

Stockholm convention
Not applicable

Rotterdam convention
Not applicable

Kyoto protocol
Not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	159 g/l
VOC Method 310	:	13.01 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	07/21/2018
Version #:	1.1
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: TREMproof® 250GC S/L LV
Material: 304511LVA 805

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 4

Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A
Aspiration Hazard	Category 1

Unknown toxicity - Health

Acute toxicity, oral	22.59 %
Acute toxicity, dermal	31.86 %
Acute toxicity, inhalation, vapor	99.93 %
Acute toxicity, inhalation, dust or mist	59.95 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	95.59 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement:
Combustible liquid.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
May be fatal if swallowed and enters airways.
Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Wash contaminated clothing before reuse. In case of fire: Use… to extinguish.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Aromatic process oil	64741-62-4	30 - 60%
Calcium Carbonate (Limestone)	1317-65-3	10 - 30%
Polyvinyl chloride	9002-86-2	5 - 10%
Petroleum distillates	64742-47-8	3 - 7%
Calcium oxide	1305-78-8	1 - 5%
Carbon Black	1333-86-4	1 - 5%
Xylene	1330-20-7	1 - 5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Ethylbenzene	100-41-4	0.1 - 1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Inhalation: Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.

Skin Contact: If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store locked up. Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)

	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm	655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL		80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm	655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm	435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	**Type**	**Exposure Limit Values**	**Source**
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA		1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA		200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Petroleum distillates	TWA		525 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA		200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA		200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA		2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA		2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA		2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA		3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA		3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm	651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work

				Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm	0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:	Use personal protective equipment as required.
Eye/face protection:	Wear goggles/face shield.
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Dark brown
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	66 °C 150 °F(Setaflash Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.11
Solubility(ies)	

Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	< 20.5 mm2/s (40 °C 104 °F)

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Alcohols. Amines. Strong acids. Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:	ATEmix: 28,922.51 mg/kg

Dermal
Product: ATEmix: 7,570.63 mg/kg

Inhalation
Product: ATEmix: 3.92 mg/l

Repeated dose toxicity
Product: No data available.

Skin Corrosion/Irritation
Product: No data available.

Specified substance(s):

Petroleum distillates	in vivo (Rabbit): Irritating Experimental result, Key study
Calcium oxide	in vivo (Rabbit): Irritating Read-across from supporting substance (structural analogue or surrogate), Key study
Carbon Black	in vivo (Rabbit): Not irritant Experimental result, Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study

Serious Eye Damage/Eye Irritation
Product: No data available.
Specified substance(s):

Petroleum distillates	Rabbit, 24 - 72 hrs: Not irritating
Carbon Black	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating

Respiratory or Skin Sensitization
Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause sensitization by inhalation.

Carcinogenicity
Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Aromatic process oil	Overall evaluation: Possibly carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:	No data available.

Specified substance(s):

Petroleum distillates	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 2.9 mg/l Mortality
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality

Aquatic Invertebrates

Product:	No data available.

Specified substance(s):

Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product:	No data available.

Specified substance(s):

Aromatic process oil	NOAEL (Oncorhynchus mykiss, 28 d): 0.1 mg/l QSAR QSAR, Key study
Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product:	No data available.

Toxicity to Aquatic Plants

Product:	No data available.

Persistence and Degradability

Biodegradation

Product:	No data available.

BOD/COD Ratio

Product:	No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chemical Identity	Reportable quantity
P-chlorobenzotrifluoride	De minimis concentration: TSCA 4% One-Time Export Notification only.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity	OSHA hazard(s)
Polyvinyl chloride	Blood
	Liver
	Cancer
	Flammability
	Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Chrysene	100 lbs.
Nonane	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

Chemical Identity	Reportable quantity	Threshold Planning Quantity
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Isophorone Diisocyanate	
Ethylbenzene	1000 lbs.
Chrysene	100 lbs.
Nonane	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Isophorone Diisocyanate	500lbs
Aromatic process oil	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Polyvinyl chloride	10000 lbs
Petroleum distillates	10000 lbs
Calcium oxide	10000 lbs
Carbon Black	10000 lbs
Xylene	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Xylene
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING
Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Calcium Carbonate (Limestone)
Polyvinyl chloride
P-chlorobenzotrifluoride
Petroleum distillates
Calcium oxide
Carbon Black
Xylene
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List

Chemical Identity
Calcium Carbonate (Limestone)
Petroleum distillates
Calcium oxide
Carbon Black
Xylene
Isophorone Diisocyanate
Chrysene
Benzo(a)pyrene
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Calcium Carbonate (Limestone)
Petroleum distillates
Calcium oxide
Carbon Black
Xylene

US. Rhode Island RTK

Chemical Identity
Calcium Carbonate (Limestone)
Polyvinyl chloride
Petroleum distillates
Calcium oxide
Carbon Black
Xylene

International regulations

Montreal protocol
Not applicable

Stockholm convention
Not applicable

Rotterdam convention
Not applicable

Kyoto protocol
Not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	94 g/l
VOC Method 310	:	8.10 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	07/21/2018
Version #:	1.1
Further Information:	No data available.

Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: TREMPROOF 250 GC-SL-LV 55 GAL
Material: 304511LVA 855

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 4

Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A
Aspiration Hazard	Category 1

Unknown toxicity - Health

Acute toxicity, oral	22.59 %
Acute toxicity, dermal	31.86 %
Acute toxicity, inhalation, vapor	99.93 %
Acute toxicity, inhalation, dust or mist	59.95 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	95.59 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement:
Combustible liquid.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
May be fatal if swallowed and enters airways.
Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Wash contaminated clothing before reuse. In case of fire: Use… to extinguish.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Aromatic process oil	64741-62-4	30 - 60%
Calcium Carbonate (Limestone)	1317-65-3	10 - 30%
Polyvinyl chloride	9002-86-2	5 - 10%
Petroleum distillates	64742-47-8	3 - 7%
Calcium oxide	1305-78-8	1 - 5%
Carbon Black	1333-86-4	1 - 5%
Xylene	1330-20-7	1 - 5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Ethylbenzene	100-41-4	0.1 - 1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Inhalation: Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.

Skin Contact: If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store locked up. Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)

	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm	655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL		80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm	655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm	435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	**Type**	**Exposure Limit Values**	**Source**
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA		1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA		200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Petroleum distillates	TWA		525 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA		200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA		200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA		2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA		2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA		2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA		3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA		3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm	651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work

				Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm	0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:	Use personal protective equipment as required.
Eye/face protection:	Wear goggles/face shield.
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Dark brown
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	66 °C 150 °F(Setaflash Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.11
Solubility(ies)	

Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	< 20.5 mm2/s (40 °C 104 °F)

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Alcohols. Amines. Strong acids. Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Causes mild skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:	ATEmix: 28,922.51 mg/kg

Dermal
Product: ATEmix: 7,570.63 mg/kg

Inhalation
Product: ATEmix: 3.92 mg/l

Repeated dose toxicity
Product: No data available.

Skin Corrosion/Irritation
Product: No data available.

Specified substance(s):

Petroleum distillates	in vivo (Rabbit): Irritating Experimental result, Key study
Calcium oxide	in vivo (Rabbit): Irritating Read-across from supporting substance (structural analogue or surrogate), Key study
Carbon Black	in vivo (Rabbit): Not irritant Experimental result, Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study

Serious Eye Damage/Eye Irritation
Product: No data available.
Specified substance(s):

Petroleum distillates	Rabbit, 24 - 72 hrs: Not irritating
Carbon Black	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating

Respiratory or Skin Sensitization
Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause sensitization by inhalation.

Carcinogenicity
Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Aromatic process oil	Overall evaluation: Possibly carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:	No data available.

Specified substance(s):

Petroleum distillates	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 2.9 mg/l Mortality
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality

Aquatic Invertebrates

Product:	No data available.

Specified substance(s):

Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product:	No data available.

Specified substance(s):

Aromatic process oil	NOAEL (Oncorhynchus mykiss, 28 d): 0.1 mg/l QSAR QSAR, Key study
Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product:	No data available.

Toxicity to Aquatic Plants

Product:	No data available.

Persistence and Degradability

Biodegradation

Product:	No data available.

BOD/COD Ratio

Product:	No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chemical Identity	Reportable quantity
P-chlorobenzotrifluoride	De minimis concentration: TSCA 4% One-Time Export Notification only.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity	OSHA hazard(s)
Polyvinyl chloride	Blood
	Liver
	Cancer
	Flammability
	Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Chrysene	100 lbs.
Nonane	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

Chemical Identity	Reportable quantity	Threshold Planning Quantity
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Isophorone Diisocyanate	
Ethylbenzene	1000 lbs.
Chrysene	100 lbs.
Nonane	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Isophorone Diisocyanate	500lbs
Aromatic process oil	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Polyvinyl chloride	10000 lbs
Petroleum distillates	10000 lbs
Calcium oxide	10000 lbs
Carbon Black	10000 lbs
Xylene	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Xylene
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING
Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Calcium Carbonate (Limestone)
Polyvinyl chloride
P-chlorobenzotrifluoride
Petroleum distillates
Calcium oxide
Carbon Black
Xylene
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List

Chemical Identity
Calcium Carbonate (Limestone)
Petroleum distillates
Calcium oxide
Carbon Black
Xylene
Isophorone Diisocyanate
Chrysene
Benzo(a)pyrene
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Calcium Carbonate (Limestone)
Petroleum distillates
Calcium oxide
Carbon Black
Xylene

US. Rhode Island RTK

Chemical Identity
Calcium Carbonate (Limestone)
Polyvinyl chloride
Petroleum distillates
Calcium oxide
Carbon Black
Xylene

International regulations

Montreal protocol
Not applicable

Stockholm convention
Not applicable

Rotterdam convention
Not applicable

Kyoto protocol
Not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	94 g/l
VOC Method 310	:	8.10 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	07/21/2018
Version #:	1.1
Further Information:	No data available.

Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: TREMPROOF 250 GC-T 2 GAL PAIL
Material: 304508A 802

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	20.61 %
Acute toxicity, dermal	29.24 %
Acute toxicity, inhalation, vapor	99.8 %
Acute toxicity, inhalation, dust or mist	55.88 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	89.36 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement:
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
Harmful to aquatic life.

Precautionary Statements

Prevention: Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Wash contaminated clothing before reuse.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*

Aromatic process oil	64741-62-4	30 - 60%
Petroleum distillates	64742-47-8	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	7 - 13%
Carbon Black	1333-86-4	5 - 10%
Polyvinyl chloride	9002-86-2	5 - 10%
Calcium oxide	1305-78-8	1 - 5%
Xylene	1330-20-7	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Ethylbenzene	100-41-4	0.1 - 1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Nonane	111-84-2	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation: Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.

Skin Contact: If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up: Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.

Conditions for safe storage, including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
Calcium Carbonate	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air

(Limestone) - Total dust.				Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA		3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL		3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA		1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA		50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA		15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA		15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA		5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium oxide	TWA		2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm	655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm	655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL		80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)

	STEL	150 ppm	655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm	435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Nonane	TWA	200 ppm		US. ACGIH Threshold Limit Values (02 2012)

Chemical name	**Type**	**Exposure Limit Values**	**Source**
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Petroleum distillates	TWA	525 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA		3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA		3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA		1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium oxide	TWA		2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA		2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA		2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm	651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Isophorone Diisocyanate	TWA	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm	0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information: Use personal protective equipment as required.

Eye/face protection: Wear goggles/face shield.

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance	
Physical state:	solid
Form:	Paste
Color:	Dark brown
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	54 °C 130 °F(Setaflash Closed Cup)
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.11
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous reactions: No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.

Hazardous Decomposition Products: Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.

Skin Contact: Causes mild skin irritation. May cause an allergic skin reaction.

Eye contact: Eye contact is possible and should be avoided.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Aromatic process oil	LD 50 (Rat): 4,320 mg/kg
Petroleum distillates	LD 50 (Rat): > 5,000 mg/kg
Carbon Black	LD 50 (Rat): > 8,000 mg/kg
Calcium oxide	LD 50 (Rat): 790 mg/kg
Xylene	LD 50 (Rat): 3,523 mg/kg
Isophorone Diisocyanate	LD 50 (Rat): 4,814 mg/kg
Ethylbenzene	LD 50 (Rat): 3,500 mg/kg
Hydrotreated heavy naphthenic distillate	LD 50 (Rat): > 5,000 mg/kg
Nonane	LD 50 (Rat): > 5,000 mg/kg

Dermal
Product: ATEmix: 6,057.09 mg/kg

Inhalation
Product: ATEmix: 4.59 mg/l

Repeated dose toxicity
Product: No data available.

Skin Corrosion/Irritation
Product: No data available.

Specified substance(s):

Petroleum distillates	in vivo (Rabbit): Irritating Experimental result, Key study
Carbon Black	in vivo (Rabbit): Not irritant Experimental result, Key study
Calcium oxide	in vivo (Rabbit): Irritating Read-across from supporting substance (structural analogue or surrogate), Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
Nonane	in vivo (Rabbit): Irritating Read-across based on grouping of substances (category approach), Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Petroleum distillates	Rabbit, 24 - 72 hrs: Not irritating
Carbon Black	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating
Nonane	Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Aromatic process oil	Overall evaluation: Possibly carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:	No data available.

Specified substance(s):

Petroleum distillates	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 2.9 mg/l Mortality
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality

Aquatic Invertebrates

Product:	No data available.

Specified substance(s):

Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product:	No data available.

Specified substance(s):

Aromatic process oil	NOAEL (Oncorhynchus mykiss, 28 d): 0.1 mg/l QSAR QSAR, Key study
Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product:	No data available.

Toxicity to Aquatic Plants

Product:	No data available.

Persistence and Degradability

Biodegradation

Product:	No data available.

BOD/COD Ratio

Product:	No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Nonane	Log Kow: 5.46

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

UN1139, COATING SOLUTION, 3, PG III

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity	OSHA hazard(s)
Polyvinyl chloride	Blood
	Liver
	Cancer
	Flammability
	Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Nonane	100 lbs.
Chrysene	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

Chemical Identity	Reportable quantity	Threshold Planning Quantity
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Isophorone Diisocyanate	
Ethylbenzene	1000 lbs.
Nonane	100 lbs.
Chrysene	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Isophorone Diisocyanate	500lbs
Aromatic process oil	10000 lbs
Petroleum distillates	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Carbon Black	10000 lbs
Polyvinyl chloride	10000 lbs
Calcium oxide	10000 lbs
Xylene	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Nonane	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING
Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Petroleum distillates
Calcium Carbonate (Limestone)
Carbon Black
Polyvinyl chloride
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List

Chemical Identity

Petroleum distillates
Calcium Carbonate (Limestone)
Carbon Black
Calcium oxide
Isophorone Diisocyanate
Chrysene
Benzo(a)pyrene
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Petroleum distillates
Calcium Carbonate (Limestone)
Carbon Black
Calcium oxide

US. Rhode Island RTK

Chemical Identity
Petroleum distillates
Calcium Carbonate (Limestone)
Carbon Black
Polyvinyl chloride
Calcium oxide

International regulations

Montreal protocol
Not applicable

Stockholm convention
Not applicable

Rotterdam convention
Not applicable

Kyoto protocol
Not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	157 g/l
VOC Method 310	:	14.16 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	07/21/2018
Version #:	1.1
Further Information:	No data available.

Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: TREMPROOF 250 GC-T 5 GAL PAIL
Material: 304508A 805

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	20.61 %
Acute toxicity, dermal	29.24 %
Acute toxicity, inhalation, vapor	99.8 %
Acute toxicity, inhalation, dust or mist	55.88 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	89.36 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement:
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.
Harmful to aquatic life.

Precautionary Statements

Prevention: Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Wash contaminated clothing before reuse.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*

Aromatic process oil	64741-62-4	30 - 60%
Petroleum distillates	64742-47-8	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	7 - 13%
Carbon Black	1333-86-4	5 - 10%
Polyvinyl chloride	9002-86-2	5 - 10%
Calcium oxide	1305-78-8	1 - 5%
Xylene	1330-20-7	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Ethylbenzene	100-41-4	0.1 - 1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Nonane	111-84-2	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation: Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.

Skin Contact: If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up: Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.

Conditions for safe storage, including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
Calcium Carbonate	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air

(Limestone) - Total dust.				Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA		3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL		3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA		1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA		50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA		15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA		15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA		5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium oxide	TWA		2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm	655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm	655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL		80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)

	STEL	150 ppm	655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm	435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Nonane	TWA	200 ppm		US. ACGIH Threshold Limit Values (02 2012)

Chemical name	**Type**	**Exposure Limit Values**	**Source**
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Petroleum distillates	TWA	525 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA		3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA		3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA		1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium oxide	TWA		2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA		2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA		2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm	651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Isophorone Diisocyanate	TWA	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm	0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information: Use personal protective equipment as required.

Eye/face protection: Wear goggles/face shield.

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance	
Physical state:	solid
Form:	Paste
Color:	Dark brown
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	54 °C 130 °F(Setaflash Closed Cup)
Evaporation rate:	Slower than n-Butyl Acetate
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.11
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous reactions: No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.

Hazardous Decomposition Products: Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.

Skin Contact: Causes mild skin irritation. May cause an allergic skin reaction.

Eye contact: Eye contact is possible and should be avoided.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Aromatic process oil	LD 50 (Rat): 4,320 mg/kg
Petroleum distillates	LD 50 (Rat): > 5,000 mg/kg
Carbon Black	LD 50 (Rat): > 8,000 mg/kg
Calcium oxide	LD 50 (Rat): 790 mg/kg
Xylene	LD 50 (Rat): 3,523 mg/kg
Isophorone Diisocyanate	LD 50 (Rat): 4,814 mg/kg
Ethylbenzene	LD 50 (Rat): 3,500 mg/kg
Hydrotreated heavy naphthenic distillate	LD 50 (Rat): > 5,000 mg/kg
Nonane	LD 50 (Rat): > 5,000 mg/kg

Dermal
Product: ATEmix: 6,057.09 mg/kg

Inhalation
Product: ATEmix: 4.59 mg/l

Repeated dose toxicity
Product: No data available.

Skin Corrosion/Irritation
Product: No data available.

Specified substance(s):

Petroleum distillates	in vivo (Rabbit): Irritating Experimental result, Key study
Carbon Black	in vivo (Rabbit): Not irritant Experimental result, Key study
Calcium oxide	in vivo (Rabbit): Irritating Read-across from supporting substance (structural analogue or surrogate), Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
Nonane	in vivo (Rabbit): Irritating Read-across based on grouping of substances (category approach), Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Petroleum distillates	Rabbit, 24 - 72 hrs: Not irritating
Carbon Black	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating
Nonane	Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Aromatic process oil	Overall evaluation: Possibly carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:	No data available.

Specified substance(s):

Petroleum distillates	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 2.9 mg/l Mortality
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality

Aquatic Invertebrates

Product:	No data available.

Specified substance(s):

Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product:	No data available.

Specified substance(s):

Aromatic process oil	NOAEL (Oncorhynchus mykiss, 28 d): 0.1 mg/l QSAR QSAR, Key study
Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product:	No data available.

Toxicity to Aquatic Plants

Product:	No data available.

Persistence and Degradability

Biodegradation

Product:	No data available.

BOD/COD Ratio

Product:	No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Xylene	Log Kow: 3.12 - 3.20
Ethylbenzene	Log Kow: 3.15
Nonane	Log Kow: 5.46

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

UN1139, COATING SOLUTION, 3, PG III

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity	OSHA hazard(s)
Polyvinyl chloride	Blood
	Liver
	Cancer
	Flammability
	Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Nonane	100 lbs.
Chrysene	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

Chemical Identity	Reportable quantity	Threshold Planning Quantity
Isophorone Diisocyanate	500 lbs.	500 lbs.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Xylene	100 lbs.
Isophorone Diisocyanate	
Ethylbenzene	1000 lbs.
Nonane	100 lbs.
Chrysene	100 lbs.
Benzo(a)pyrene	1 lbs.
Toluene	1000 lbs.
Methanol	5000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Isophorone Diisocyanate	500lbs
Aromatic process oil	10000 lbs
Petroleum distillates	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Carbon Black	10000 lbs
Polyvinyl chloride	10000 lbs
Calcium oxide	10000 lbs
Xylene	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Nonane	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Ethylbenzene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING
Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Petroleum distillates
Calcium Carbonate (Limestone)
Carbon Black
Polyvinyl chloride
Calcium oxide
Ethylbenzene
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List

Chemical Identity

Petroleum distillates
Calcium Carbonate (Limestone)
Carbon Black
Calcium oxide
Isophorone Diisocyanate
Chrysene
Benzo(a)pyrene
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Petroleum distillates
Calcium Carbonate (Limestone)
Carbon Black
Calcium oxide

US. Rhode Island RTK

Chemical Identity
Petroleum distillates
Calcium Carbonate (Limestone)
Carbon Black
Polyvinyl chloride
Calcium oxide

International regulations

Montreal protocol
Not applicable

Stockholm convention
Not applicable

Rotterdam convention
Not applicable

Kyoto protocol
Not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	157 g/l
VOC Method 310	:	14.16 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	07/21/2018
Version #:	1.1
Further Information:	No data available.

Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.