Water Features (PUMA)

Table of Contents

Tremco PUMA BC LM SDS 1

Tremco PUMA BC SDS 15

Tremco PUMA BC T SDS 29

Tremco PUMA Cleaner SDS 43

Tremco PUMA Filler Powder SDS 56

Tremco PUMA Flashing SDS 68

Tremco PUMA Initiator SDS 84

Tremco PUMA Primer SDS 98

Tremco PUMA TC Clear SDS 112

Tremco PUMA TC Decorative SDS 126

Tremco PUMA TC Gray SDS 140

Tremco PUMA TC Slate Gray SDS 154

Tremco PUMA TC Tintable SDS 168

Tremco PUMA WC SDS 182

SAFETY DATA SHEET

1. Identification

Material name: Tremco PUMA BC LM - 6 GAL
Material: 470371 805

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 2

Health Hazards

Serious Eye Damage/Eye Irritation	Category 2A
Skin sensitizer	Category 1

Unknown toxicity - Health

Acute toxicity, oral	4 %
Acute toxicity, dermal	6 %
Acute toxicity, inhalation, vapor	71.9 %
Acute toxicity, inhalation, dust or mist	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement:	Highly flammable liquid and vapor. Causes serious eye irritation. May cause an allergic skin reaction.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace.
Response:	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse. In case of fire: Use … to extinguish.
Storage:	Store in well-ventilated place. Keep cool.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Barium sulfate	7727-43-7	30 - 60%
Methyl methacrylate	80-62-6	15 - 40%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Rinse mouth thoroughly.
Inhalation:	Move to fresh air.

Skin Contact: Get medical attention if symptoms occur. Take off immediately all contaminated clothing. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Get medical attention if symptoms occur.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Barium sulfate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (02 2014)
Barium sulfate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Barium sulfate - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Barium sulfate - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Methyl methacrylate	TWA	50 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 410 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Barium sulfate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Barium sulfate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Barium sulfate	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Barium sulfate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Barium sulfate - Respirable dust.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Methyl methacrylate	TWA	50 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl methacrylate	TWA	50 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methyl methacrylate	TWA	50 ppm 205 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:

Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof ventilation equipment.

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection:

Use suitable protective gloves if risk of skin contact.

Other:

Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection:

In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Gray
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	100 °C 212 °F
Flash Point:	11.5 °C 52.7 °F(Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	12.5 %(V)
Flammability limit - lower (%):	2.1 %(V)
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.23
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Alcohols. Amines. Strong acids. Strong bases. Water, moisture.

Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May cause an allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Barium sulfate	LD 50 (Rat): 364 g/kg
Methyl methacrylate	LD 50 (Rat): 7,900 mg/kg

Dermal

Product:	ATEmix: 6,430.87 mg/kg

Inhalation

Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Methyl methacrylate	LC 50 (Rat): 29.8 mg/l

Repeated dose toxicity

Product:	No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Barium sulfate	validated "in vitro" test method Not irritant Read-across from supporting substance (structural analogue or surrogate), Key study
Methyl methacrylate	in vivo (Rabbit): irritating after 4/24h occluded exposure Experimental result, Weight of Evidence study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Barium sulfate	Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):
Methyl methacrylate — LC 50 (Fathead minnow (Pimephales promelas), 96 h): 130 mg/l Mortality

Aquatic Invertebrates
Product: No data available.

Specified substance(s):
Barium sulfate — EC 50 (Tubificid worm (Tubifex tubifex), 24 h): 34.2 - 57.71 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):
Barium sulfate — LC 1 (Oncorhynchus mykiss, 28 d): 2,813 µg/l Experimental result, Supporting study
LC 50 (Oncorhynchus mykiss, 28 d): 42,700 µg/l Experimental result, Supporting study
LC 10 (Oncorhynchus mykiss, 28 d): 9,543 µg/l Experimental result, Supporting study

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Specified substance(s):
Methyl methacrylate Log Kow: 1.38

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1866, RESIN SOLUTION, 3, PG II

CFR / DOT:

UN1866, Resin solution, 3, PG II

IMDG:

UN1866, RESIN SOLUTION, 3, PG II

Further Information:
The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)
None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Barium sulfate	1000 lbs.
Methyl methacrylate	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Barium sulfate	1000 lbs.
Methyl methacrylate	1000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Barium sulfate	10000 lbs
Methyl methacrylate	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Methyl methacrylate

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

No ingredient regulated by CA Prop 65 present.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Barium sulfate
Methyl methacrylate

US. Massachusetts RTK - Substance List

Chemical Identity
Barium sulfate
Methyl methacrylate

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Barium sulfate
Methyl methacrylate

US. Rhode Island RTK

Chemical Identity
Methyl methacrylate

International regulations

Montreal protocol
not applicable

Stockholm convention
not applicable

Rotterdam convention
not applicable

Kyoto protocol
not applicable

VOC: When appropriately mixed with the other part, product has a VOC less water and exempt solvent of: 0 g/l

Regulatory VOC (less water and exempt solvent)	:	0 g/l 0 g/l
VOC Method 310	:	0.00 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	02/17/2017
Version #:	2.0
Further Information:	No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: Tremco PUMA BC - 6 GAL
Material: 470370 805

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 2

Health Hazards

Serious Eye Damage/Eye Irritation	Category 2A
Skin sensitizer	Category 1

Unknown toxicity - Health

Acute toxicity, oral	3.7 %
Acute toxicity, dermal	5.7 %
Acute toxicity, inhalation, vapor	68.3 %
Acute toxicity, inhalation, dust or mist	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement:	Highly flammable liquid and vapor. Causes serious eye irritation. May cause an allergic skin reaction.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace.
Response:	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse. In case of fire: Use … to extinguish.
Storage:	Store in well-ventilated place. Keep cool.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Methyl methacrylate	80-62-6	30 - 60%
Barium sulfate	7727-43-7	30 - 60%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Rinse mouth thoroughly.
Inhalation:	Move to fresh air.

Skin Contact: Get medical attention if symptoms occur. Take off immediately all contaminated clothing. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Get medical attention if symptoms occur.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 410 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (02 2014)
Barium sulfate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Barium sulfate - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Barium sulfate - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)

Chemical name	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	100 ppm	Canada. British Columbia OELs. (Occupational

				Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl methacrylate	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methyl methacrylate	TWA	50 ppm	205 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Barium sulfate - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Barium sulfate - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Barium sulfate	TWA		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Barium sulfate - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Barium sulfate - Respirable dust.	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof ventilation equipment.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Off-white
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	100.3 °C 212.5 °F
Flash Point:	11.5 °C 52.7 °F(Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	12.5 %(V)
Flammability limit - lower (%):	2.1 %(V)
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.3
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Alcohols. Amines. Strong acids. Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May cause an allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Methyl methacrylate	LD 50 (Rat): 7,900 mg/kg
Barium sulfate	LD 50 (Rat): 364 g/kg

Dermal

Product:	ATEmix: 6,430.87 mg/kg

Inhalation

Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Methyl methacrylate	LC 50 (Rat): 29.8 mg/l

Repeated dose toxicity

Product:	No data available.

Skin Corrosion/Irritation

Product:	No data available.

Specified substance(s):

Methyl methacrylate	in vivo (Rabbit): irritating after 4/24h occluded exposure Experimental result, Weight of Evidence study
Barium sulfate	validated "in vitro" test method Not irritant Read-across from supporting substance (structural analogue or surrogate), Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Barium sulfate	Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):
Methyl methacrylate — LC 50 (Fathead minnow (Pimephales promelas), 96 h): 130 mg/l Mortality

Aquatic Invertebrates
Product: No data available.

Specified substance(s):
Barium sulfate — EC 50 (Tubificid worm (Tubifex tubifex), 24 h): 34.2 - 57.71 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):
Barium sulfate — LC 1 (Oncorhynchus mykiss, 28 d): 2,813 µg/l Experimental result, Supporting study
LC 50 (Oncorhynchus mykiss, 28 d): 42,700 µg/l Experimental result, Supporting study
LC 10 (Oncorhynchus mykiss, 28 d): 9,543 µg/l Experimental result, Supporting study

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Methyl methacrylate Log Kow: 1.38

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1866, RESIN SOLUTION, 3, PG II

CFR / DOT:

UN1866, Resin solution, 3, PG II

IMDG:

UN1866, RESIN SOLUTION, 3, PG II

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.
Barium sulfate	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Fire Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance
None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.
Barium sulfate	1000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Methyl methacrylate	10000 lbs
Barium sulfate	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Methyl methacrylate

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)
None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)
None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65
No ingredient regulated by CA Prop 65 present.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Methyl methacrylate
Barium sulfate

US. Massachusetts RTK - Substance List

Chemical Identity
Methyl methacrylate
Barium sulfate

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Methyl methacrylate
Barium sulfate

US. Rhode Island RTK

Chemical Identity
Methyl methacrylate

International regulations

Montreal protocol
not applicable

Stockholm convention
not applicable

Rotterdam convention
not applicable

Kyoto protocol
not applicable

VOC: When appropriately mixed with the other part, product has a VOC less water and exempt solvent of: 0 g/l

Regulatory VOC (less water and exempt solvent)	:	0 g/l
VOC Method 310	:	0.00 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	02/17/2017
Version #:	2.0
Further Information:	No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: Tremco PUMA BC T - 6 GAL
Material: 470372 805

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 2

Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
Serious Eye Damage/Eye Irritation	Category 2A
Skin sensitizer	Category 1

Unknown toxicity - Health

Acute toxicity, oral	24.05 %
Acute toxicity, dermal	26.05 %
Acute toxicity, inhalation, vapor	75.85 %
Acute toxicity, inhalation, dust or mist	80.7 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	Highly flammable liquid and vapor. Harmful if inhaled. Causes serious eye irritation. May cause an allergic skin reaction.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.
Response:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTRE/doctor/ if you feel unwell. Specific treatment (see this label). Wash contaminated clothing before reuse. In case of fire: Use … to extinguish.
Storage:	Store in well-ventilated place. Keep cool.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Methyl methacrylate	80-62-6	15 - 40%
Trade Secret	Trade Secret	15 - 40%
Barium sulfate	7727-43-7	15 - 40%
Trade Secret	Trade Secret	3 - 7%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Rinse mouth thoroughly.
Inhalation:	Move to fresh air.
Skin Contact:	Get medical attention if symptoms occur. Take off immediately all contaminated clothing. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms:	Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment:	Get medical attention if symptoms occur.

5. Fire-fighting measures

General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 410 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (02 2014)
Barium sulfate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Barium sulfate - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Barium sulfate - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Trade Secret - Respirable	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)

fraction.			
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Trade Secret - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Trade Secret - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Trade Secret	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

Chemical name	**Type**	**Exposure Limit Values**	**Source**
Methyl methacrylate	TWA	50 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl methacrylate	TWA	50 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methyl methacrylate	TWA	50 ppm 205 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Barium sulfate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Barium sulfate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Barium sulfate	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Barium sulfate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Barium sulfate - Respirable dust.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Trade Secret - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Trade Secret - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Trade Secret - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Trade Secret - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Trade Secret - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Trade Secret - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Trade Secret - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)

Appropriate Engineering Controls Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof ventilation equipment.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: liquid
Color: Beige
Odor: Mild petroleum/solvent
Odor threshold: No data available.
pH: No data available.
Melting point/freezing point: No data available.
Initial boiling point and boiling range: 100 °C 212 °F
Flash Point: 11.5 °C 52.7 °F(Setaflash Closed Cup)
Evaporation rate: Slower than Ether
Flammability (solid, gas): No
Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):	12.5 %(V)
Flammability limit - lower (%):	2.1 %(V)
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.36
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May cause an allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral
Product: Not classified for acute toxicity based on available data.

Dermal
Product: ATEmix: 7,663.21 mg/kg

Inhalation
Product: ATEmix: 2.3 mg/l

Repeated dose toxicity
Product: No data available.

Skin Corrosion/Irritation
Product: No data available.

Serious Eye Damage/Eye Irritation
Product: No data available.

Respiratory or Skin Sensitization
Product: No data available.

Carcinogenicity
Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:
No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:
No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):
No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Aquatic Invertebrates
Product: No data available.

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1866, RESIN SOLUTION, 3, PG II

CFR / DOT:

UN1866, Resin solution, 3, PG II

IMDG:

UN1866, RESIN SOLUTION, 3, PG II

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.
Barium sulfate	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.
Barium sulfate	1000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Methyl methacrylate	10000 lbs
Trade Secret	10000 lbs
Barium sulfate	10000 lbs
Trade Secret	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Methyl methacrylate

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

No ingredient regulated by CA Prop 65 present.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Methyl methacrylate
Barium sulfate

US. Massachusetts RTK - Substance List

Chemical Identity
Methyl methacrylate
Barium sulfate

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Methyl methacrylate
Barium sulfate
Trade Secret

US. Rhode Island RTK

Chemical Identity
Methyl methacrylate

International regulations

Montreal protocol

not applicable

Stockholm convention

not applicable

Rotterdam convention

not applicable

Kyoto protocol

not applicable

VOC: When appropriately mixed with the other part, product has a VOC less water and exempt solvent of: 0 g/l

Regulatory VOC (less water and exempt solvent)	:	0 g/l 0 g/l
VOC Method 310	:	0.00 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	02/17/2017
Version #:	2.0
Further Information:	No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: Tremco PUMA Cleaner - 6 GAL
Material: 470080 805

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 2

Health Hazards

Serious Eye Damage/Eye Irritation	Category 2A
Skin sensitizer	Category 1

Unknown toxicity - Health

Acute toxicity, oral	0 %
Acute toxicity, dermal	0 %
Acute toxicity, inhalation, vapor	0 %
Acute toxicity, inhalation, dust or mist	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement:	Highly flammable liquid and vapor. Causes serious eye irritation. May cause an allergic skin reaction.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace.
Response:	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse. In case of fire: Use … to extinguish.
Storage:	Store in well-ventilated place. Keep cool.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Methyl methacrylate	80-62-6	60 - 100%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Rinse mouth thoroughly.
Inhalation:	Move to fresh air.
Skin Contact:	Get medical attention if symptoms occur. Take off immediately all contaminated clothing. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Get medical attention if symptoms occur.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 410 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl methacrylate	TWA	50 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methyl methacrylate	TWA	50 ppm 205 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:	Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof ventilation equipment.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Colorless
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	100.3 °C 212.5 °F
Flash Point:	11.5 °C 52.7 °F(Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	12.5 %(V)
Flammability limit - lower (%):	2.1 %(V)
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	0.94
Solubility(ies)	

Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May cause an allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Methyl methacrylate	LD 50 (Rat): 7,900 mg/kg

Dermal

Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Methyl methacrylate	LD 50 (Rabbit): > 5,000 mg/kg

Inhalation

Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Methyl methacrylate	LC 50 (Rat): 29.8 mg/l

Repeated dose toxicity

Product:	No data available.

Skin Corrosion/Irritation

Product:	No data available.

Specified substance(s):

Methyl methacrylate	in vivo (Rabbit): irritating after 4/24h occluded exposure Experimental result, Weight of Evidence study

Serious Eye Damage/Eye Irritation

Product:	No data available.

Respiratory or Skin Sensitization

Product:	No data available.

Carcinogenicity

Product:	No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:
No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:
No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):
No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):
Methyl methacrylate LC 50 (Fathead minnow (Pimephales promelas), 96 h): 130 mg/l Mortality

Aquatic Invertebrates
Product: No data available.

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Specified substance(s):
Methyl methacrylate Log Kow: 1.38

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1247, METHYL METHACRYLATE MONOMER, STABILIZED, 3, PG II

CFR / DOT:

UN1247, Methyl methacrylate monomer, stabilized, 3, PG II

IMDG:

UN1247, METHYL METHACRYLATE MONOMER, STABILIZED, 3, PG II

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Methyl methacrylate	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Methyl methacrylate

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

No ingredient regulated by CA Prop 65 present.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Methyl methacrylate

US. Massachusetts RTK - Substance List

Chemical Identity
Methyl methacrylate

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Methyl methacrylate

US. Rhode Island RTK

Chemical Identity
Methyl methacrylate

International regulations

Montreal protocol
not applicable

Stockholm convention
not applicable

Rotterdam convention
not applicable

Kyoto protocol
not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	0 g/l
VOC Method 310	:	0.00 %

Inventory Status:

Australia AICS:	All components in this product are listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	All components in this product are listed on or exempt from the Inventory.
Japan (ENCS) List:	All components in this product are listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	All components in this product are listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	All components in this product are listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	All components in this product are listed on or exempt from the Inventory.
Japan ISHL Listing:	All components in this product are listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	02/17/2017
Version #:	2.0
Further Information:	No data available.

Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: Tremco PUMA Filler Powder - 55LB Bag
Material: 470100 501

Recommended use and restriction on use

Recommended use: Pigment
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	100 %
Acute toxicity, dermal	100 %
Acute toxicity, inhalation, vapor	100 %
Acute toxicity, inhalation, dust or mist	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: May cause cancer.

Precautionary Statements

Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If exposed or concerned: Get medical advice/attention.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	60 - 100%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Rinse mouth thoroughly.

Inhalation: Move to fresh air.

Skin Contact: Remove contaminated clothing and wash the skin thoroughly with soap and water after work.

Eye contact: Rinse immediately with plenty of water.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: No data available.

Methods and material for containment and cleaning up: Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. Environmental manager must be informed of all major spillages.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.

Conditions for safe storage, including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand	PEL	0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA	2.4 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

Chemical name	Type	Exposure Limit Values	Source
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information: Use personal protective equipment as required.

Eye/face protection: Wear goggles/face shield.

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: No data available.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Appearance

Physical state: solid
Form: Powder
Color: Off-white
Odor: Odorless
Odor threshold: No data available.
pH: No data available.
Melting point/freezing point: No data available.
Initial boiling point and boiling range: No data available.
Flash Point: No data available.
Evaporation rate: No data available.
Flammability (solid, gas): No
Upper/lower limit on flammability or explosive limits
Flammability limit - upper (%): No data available.

Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	No data available.
Relative density:	1.4
Solubility(ies)	
Solubility in water:	Miscible with water.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Moderately irritating to skin with prolonged exposure.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral
Product:

Dermal
Product:

Inhalation
Product:

Repeated dose toxicity
Product: No data available.

Skin Corrosion/Irritation
Product: No data available.

Serious Eye Damage/Eye Irritation
Product: No data available.

Respiratory or Skin Sensitization
Product: No data available.

Carcinogenicity
Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Crystalline Silica (Quartz)/ Silica Sand	Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Crystalline (Quartz)/ Sand	Silica	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):
No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Aquatic Invertebrates
Product: No data available.

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)
None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):
None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance
None present or none present in regulated quantities.

SARA 304 Emergency Release Notification
None present or none present in regulated quantities.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Crystalline Silica (Quartz)/ Silica Sand	10000 lbs

SARA 313 (TRI Reporting)
None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)
None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)
None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65
This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Crystalline Silica (Quartz)/ Silica Sand	Carcinogenic. 09 2011

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Crystalline Silica (Quartz)/ Silica Sand

US. Massachusetts RTK - Substance List

Chemical Identity
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Crystalline Silica (Quartz)/ Silica Sand

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

not applicable

Stockholm convention

not applicable

Rotterdam convention

not applicable

Kyoto protocol

not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	0 g/l
VOC Method 310	:	0.00 %

Inventory Status:

Australia AICS:	All components in this product are listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	All components in this product are listed on or exempt from the Inventory.
Japan (ENCS) List:	All components in this product are listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	All components in this product are listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	All components in this product are listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	All components in this product are listed on or exempt from the Inventory.
Japan ISHL Listing:	All components in this product are listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	02/17/2017
Version #:	2.0
Further Information:	No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: Tremco PUMA Flashing – 2 GAL
Material: 470373 802

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 1

Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
Serious Eye Damage/Eye Irritation	Category 2A
Skin sensitizer	Category 1

Unknown toxicity - Health

Acute toxicity, oral	4.75 %
Acute toxicity, dermal	26.05 %
Acute toxicity, inhalation, vapor	74.35 %
Acute toxicity, inhalation, dust or mist	80.7 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	Extremely flammable liquid and vapor. Harmful if inhaled. Causes serious eye irritation. May cause an allergic skin reaction.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.
Response:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTRE/doctor/ if you feel unwell. Specific treatment (see this label). Wash contaminated clothing before reuse. In case of fire: Use … to extinguish.
Storage:	Store in well-ventilated place. Keep cool.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Methyl methacrylate	80-62-6	15 - 40%
Aluminum hydroxide	21645-51-2	15 - 40%
Barium sulfate	7727-43-7	15 - 40%
Silicon dioxide, amorphous	112945-52-5	1 - 5%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Rinse mouth thoroughly.
Inhalation:	Move to fresh air.
Skin Contact:	Get medical attention if symptoms occur. Take off immediately all contaminated clothing. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms:	Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment:	Get medical attention if symptoms occur.

5. Fire-fighting measures

General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 410 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (02 2014)
Barium sulfate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Barium sulfate - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Barium sulfate - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum hydroxide -	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)

Respirable fraction.			
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum hydroxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum hydroxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Silicon dioxide, amorphous	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

Chemical name	**Type**	**Exposure Limit Values**	**Source**
Methyl methacrylate	TWA	50 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl methacrylate	TWA	50 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Methyl methacrylate	TWA	50 ppm	205 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Barium sulfate - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Barium sulfate - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Barium sulfate	TWA		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Barium sulfate - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Barium sulfate - Respirable dust.	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Aluminum hydroxide - Respirable.	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum hydroxide - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum hydroxide - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum hydroxide - Respirable fraction.	TWA		1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Aluminum hydroxide - Inhalable fraction.	TWA		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum hydroxide - Respirable fraction.	TWA		3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum hydroxide - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:

Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof ventilation equipment.

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection:

Use suitable protective gloves if risk of skin contact.

Other:

Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Gray
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	11.5 °C 52.7 °F(ISO 1516 (Pensky-Martens (A and B Closed Cup)))
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	38.7 mbar (20 °C 68 °F)
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.36
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.

Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May cause an allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Methyl methacrylate	LD 50 (Rat): 7,900 mg/kg
Aluminum hydroxide	LD 50 (Rat): > 2,000 mg/kg
Barium sulfate	LD 50 (Rat): 364 g/kg
Silicon dioxide, amorphous	LD 50 (Rat): 5,001 mg/kg

Dermal

Product:	ATEmix: 7,663.21 mg/kg

Inhalation
Product: ATEmix: 2.3 mg/l

Repeated dose toxicity
Product: No data available.

Skin Corrosion/Irritation
Product: No data available.

Specified substance(s):

Methyl methacrylate	in vivo (Rabbit): irritating after 4/24h occluded exposure Experimental result, Weight of Evidence study
Aluminum hydroxide	in vivo (Rabbit): Not classified as an Irritant Experimental result, Key study
Barium sulfate	validated "in vitro" test method Not irritant Read-across from supporting substance (structural analogue or surrogate), Key study

Serious Eye Damage/Eye Irritation
Product: No data available.
Specified substance(s):

Aluminum hydroxide	Rabbit, 24 hrs: Not irritating
Barium sulfate	Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization
Product: No data available.

Carcinogenicity
Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:
No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:
No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):
No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):
Methyl methacrylate — LC 50 (Fathead minnow (Pimephales promelas), 96 h): 130 mg/l Mortality

Aquatic Invertebrates
Product: No data available.

Specified substance(s):
Barium sulfate — EC 50 (Tubificid worm (Tubifex tubifex), 24 h): 34.2 - 57.71 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):

Barium sulfate	LC 1 (Oncorhynchus mykiss, 28 d): 2,813 µg/l Experimental result, Supporting study LC 50 (Oncorhynchus mykiss, 28 d): 42,700 µg/l Experimental result, Supporting study LC 10 (Oncorhynchus mykiss, 28 d): 9,543 µg/l Experimental result, Supporting study

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Specified substance(s):

Methyl methacrylate	Log Kow: 1.38

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1866, RESIN SOLUTION, 3, PG II

CFR / DOT:

UN1866, Resin solution, 3, PG II

IMDG:

UN1866, RESIN SOLUTION, 3, PG II

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.
Barium sulfate	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.
Barium sulfate	1000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Methyl methacrylate	10000 lbs
Aluminum hydroxide	10000 lbs
Barium sulfate	10000 lbs
Silicon dioxide, amorphous	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Methyl methacrylate

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

No ingredient regulated by CA Prop 65 present.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Methyl methacrylate
Barium sulfate

US. Massachusetts RTK - Substance List

Chemical Identity
Methyl methacrylate
Barium sulfate
Silicon dioxide, amorphous

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Methyl methacrylate
Barium sulfate
Silicon dioxide, amorphous

US. Rhode Island RTK

Chemical Identity
Methyl methacrylate

International regulations

Montreal protocol

not applicable

Stockholm convention

not applicable

Rotterdam convention

not applicable

Kyoto protocol

not applicable

VOC: When appropriately mixed with the other part, product has a VOC less water and exempt solvent of: 0 g/l

Regulatory VOC (less water and exempt solvent)	:	348 g/l
VOC Method 310	:	25.65 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	02/17/2017
Version #:	2.0
Further Information:	No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: Tremco PUMA Initiator - 55LB Pail
Material: 470060 805

Recommended use and restriction on use

Recommended use: Pigment
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Skin Corrosion/Irritation	Category 2
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	50 %
Acute toxicity, dermal	75 %
Acute toxicity, inhalation, vapor	100 %
Acute toxicity, inhalation, dust or mist	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Causes skin irritation.
May cause an allergic skin reaction.
May cause cancer.

Precautionary Statements

Prevention: Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response: IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Dibenzoyl Peroxide	94-36-0	15 - 40%
Mica	12001-26-2	15 - 40%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	15 - 40%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTRE/doctor/ if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: Get medical attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms:	Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.

Indication of immediate medical attention and special treatment needed

Treatment:	Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards:	No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical:	During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.
Methods and material for containment and cleaning up:	Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
Notification Procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with skin. Avoid contact with eyes, skin, and clothing. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.

Conditions for safe storage, including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Dibenzoyl Peroxide	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Mica - Respirable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Mica	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand	PEL	0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

Chemical name	Type	Exposure Limit Values	Source
Dibenzoyl Peroxide	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Dibenzoyl Peroxide	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Dibenzoyl Peroxide	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Mica - Respirable.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Mica - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Mica - Respirable dust.	TWA	3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Wash contaminated clothing before reuse. Avoid contact with skin. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state:	solid
Form:	Powder
Color:	White
Odor:	Odorless
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	No data available.
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	No data available.
Relative density:	0.9
Solubility(ies)	
Solubility in water:	Miscible with water.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.

Hazardous Decomposition Products: Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.

Skin Contact: May be harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.

Eye contact: Eye contact is possible and should be avoided.

Ingestion: May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral
Product: ATEmix: 4,000 mg/kg

Dermal
Product: ATEmix: 2,000 mg/kg

Inhalation
Product:

Repeated dose toxicity
Product: No data available.

Skin Corrosion/Irritation
Product: No data available.

Specified substance(s):
Dibenzoyl Peroxide — Irritating
in vivo (Rabbit): Not irritant Experimental result, Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Dibenzoyl Peroxide	Rabbit, 1 - 48 hrs: Irritating

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Crystalline Silica (Quartz)/ Silica Sand	Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Crystalline (Quartz)/ Sand	Silica Silica	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Aquatic Invertebrates
Product: No data available.

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Specified substance(s):
Dibenzoyl Peroxide Log Kow: 3.46

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Dicyclohexyl phthalate	

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Dibenzoyl Peroxide	10000 lbs
Mica	10000 lbs
Crystalline Silica (Quartz)/ Silica Sand	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Dibenzoyl Peroxide

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Crystalline Silica (Quartz)/ Silica Sand	Carcinogenic. 09 2011

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Dibenzoyl Peroxide
Mica
Crystalline Silica (Quartz)/ Silica Sand

US. Massachusetts RTK - Substance List

Chemical Identity
Dibenzoyl Peroxide
Mica
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Dibenzoyl Peroxide
Dicyclohexyl phthalate
Mica
Crystalline Silica (Quartz)/ Silica Sand

US. Rhode Island RTK

Chemical Identity
Dibenzoyl Peroxide
Dicyclohexyl phthalate

International regulations

Montreal protocol

not applicable

Stockholm convention

not applicable

Rotterdam convention

not applicable

Kyoto protocol

not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	0 g/l
VOC Method 310	:	0.00 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	All components in this product are listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	All components in this product are listed on or exempt from the Inventory.
US TSCA Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	All components in this product are listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	02/17/2017
Version #:	2.0
Further Information:	No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: Tremco PUMA Primer - 6 GAL
Material: 470070 805

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 1

Health Hazards

Serious Eye Damage/Eye Irritation	Category 2A
Skin sensitizer	Category 1

Unknown toxicity - Health

Acute toxicity, oral	33.6 %
Acute toxicity, dermal	33.9 %
Acute toxicity, inhalation, vapor	36.9 %
Acute toxicity, inhalation, dust or mist	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement:	Extremely flammable liquid and vapor. Causes serious eye irritation. May cause an allergic skin reaction.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace.
Response:	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse. In case of fire: Use … to extinguish.
Storage:	Store in well-ventilated place. Keep cool.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Methyl methacrylate	80-62-6	60 - 100%
Ethylene glycol dimethacrylate	97-90-5	1 - 5%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Rinse mouth thoroughly.
Inhalation:	Move to fresh air.

Skin Contact: Get medical attention if symptoms occur. Take off immediately all contaminated clothing. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Get medical attention if symptoms occur.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 410 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl methacrylate	TWA	50 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methyl methacrylate	TWA	50 ppm 205 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:	Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof ventilation equipment.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Colorless
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	11.5 °C 52.7 °F
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	12.5 %(V)
Flammability limit - lower (%):	2.1 %(V)
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	0.99
Solubility(ies)	

Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May cause an allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Methyl methacrylate	LD 50 (Rat): 7,900 mg/kg
Ethylene glycol dimethacrylate	LD 50 (Rat): 8,145 mg/kg

Dermal

Product: ATEmix: 51,730.43 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Methyl methacrylate	LC 50 (Rat): 29.8 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Methyl methacrylate	in vivo (Rabbit): irritating after 4/24h occluded exposure Experimental result, Weight of Evidence study
Ethylene glycol dimethacrylate	in vivo (Rabbit): Not irritant Experimental result, Weight of Evidence study

Serious Eye Damage/Eye Irritation

Product: No data available.

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):
Methyl methacrylate LC 50 (Fathead minnow (Pimephales promelas), 96 h): 130 mg/l Mortality

Aquatic Invertebrates
Product: No data available.

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Specified substance(s):
Methyl methacrylate Log Kow: 1.38

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1866, RESIN SOLUTION, 3, PG II

CFR / DOT:

UN1866, Resin solution, 3, PG II

IMDG:

UN1866, RESIN SOLUTION, 3, PG II

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Methyl methacrylate	10000 lbs
Ethylene glycol dimethacrylate	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Methyl methacrylate

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

No ingredient regulated by CA Prop 65 present.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Methyl methacrylate

US. Massachusetts RTK - Substance List

Chemical Identity
Methyl methacrylate

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Methyl methacrylate

US. Rhode Island RTK

Chemical Identity
Methyl methacrylate

International regulations

Montreal protocol

not applicable

Stockholm convention

not applicable

Rotterdam convention

not applicable

Kyoto protocol

not applicable

VOC: When appropriately mixed with the other part, product has a VOC less water and exempt solvent of: 0 g/l

Regulatory VOC (less water and exempt solvent)	:	0 g/l
VOC Method 310	:	0.00 %

Inventory Status:

Australia AICS:	All components in this product are listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	All components in this product are listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	02/17/2017
Version #:	2.0
Further Information:	No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: Tremco PUMA TC Clear - 6 GAL
Material: 470800 805

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 2

Health Hazards

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Skin sensitizer	Category 1

Unknown toxicity - Health

Acute toxicity, oral	33 %
Acute toxicity, dermal	33 %
Acute toxicity, inhalation, vapor	64 %
Acute toxicity, inhalation, dust or mist	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Highly flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace.

Response: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse. In case of fire: Use … to extinguish.

Storage: Store in well-ventilated place. Keep cool.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Methyl methacrylate	80-62-6	30 - 60%
2-Propenoic acid, 2-ethylhexyl ester	103-11-7	15 - 40%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTRE/doctor/ if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact:	Take off immediately all contaminated clothing. Get medical attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms:	Respiratory tract irritation. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.

Indication of immediate medical attention and special treatment needed

Treatment:	Get medical attention if symptoms occur.

5. Fire-fighting measures

General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 410 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl methacrylate	TWA	50 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methyl methacrylate	TWA	50 ppm 205 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:	Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof ventilation equipment.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Violet
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	100.3 °C 212.5 °F
Flash Point:	11.5 °C 52.7 °F(Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	12.5 %(V)
Flammability limit - lower (%):	2.1 %(V)
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	0.98

Solubility(ies)

Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Causes skin irritation. May cause an allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:	ATEmix: 7,045.21 mg/kg

Dermal
Product: ATEmix: 12,181.27 mg/kg

Inhalation
Product: Not classified for acute toxicity based on available data.

Specified substance(s):
Methyl methacrylate — LC 50 (Rat): 29.8 mg/l

Repeated dose toxicity
Product: No data available.

Skin Corrosion/Irritation
Product: No data available.

Specified substance(s):
Methyl methacrylate — in vivo (Rabbit): irritating after 4/24h occluded exposure Experimental result, Weight of Evidence study

2-Propenoic acid, 2-ethylhexyl ester — in vivo (Rabbit): Irritating Experimental result, Key study

Serious Eye Damage/Eye Irritation
Product: No data available.
Specified substance(s):

2-Propenoic acid, 2-ethylhexyl ester — Rabbit, 24 - 48 hrs: Not irritating

Respiratory or Skin Sensitization
Product: No data available.

Carcinogenicity
Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:
No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:
No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):
No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):
Methyl methacrylate LC 50 (Fathead minnow (Pimephales promelas), 96 h): 130 mg/l Mortality

Aquatic Invertebrates
Product: No data available.

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Specified substance(s):
Methyl methacrylate Log Kow: 1.38

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1866, RESIN SOLUTION, 3, PG II

CFR / DOT:

UN1866, Resin solution, 3, PG II

IMDG:

UN1866, RESIN SOLUTION, 3, PG II

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.
Butyl diglycol methacrylate	

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Methyl methacrylate	10000 lbs
2-Propenoic acid, 2-ethylhexyl ester	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Methyl methacrylate
Butyl diglycol methacrylate

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

No ingredient regulated by CA Prop 65 present.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester
Butyl diglycol methacrylate

US. Massachusetts RTK - Substance List

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester
Butyl diglycol methacrylate

US. Rhode Island RTK

Chemical Identity
Methyl methacrylate
Butyl diglycol methacrylate

International regulations

Montreal protocol
not applicable

Stockholm convention
not applicable

Rotterdam convention
not applicable

Kyoto protocol
not applicable

VOC: When appropriately mixed with the other part, product has a VOC less water and exempt solvent of:
0 g/l

Regulatory VOC (less water and exempt solvent)	:	0 g/l
VOC Method 310	:	0.00 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	All components in this product are listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	08/10/2017
Version #:	3.0
Further Information:	No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: Tremco PUMA TC Decorative - 6 GAL
Material: 470900 805

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 2

Health Hazards

Acute toxicity (Oral)	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Skin sensitizer	Category 1

Unknown toxicity - Health

Acute toxicity, oral	30 %
Acute toxicity, dermal	30 %
Acute toxicity, inhalation, vapor	44.2 %
Acute toxicity, inhalation, dust or mist	99.3 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	Highly flammable liquid and vapor. Harmful if swallowed. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace.
Response:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation or rash occurs: Get medical advice/attention. IF SWALLOWED: Call a POISON CENTRE/doctor/ if you feel unwell. Rinse mouth. Specific treatment (see this label). Wash contaminated clothing before reuse. In case of fire: Use … for extinction.
Storage:	Store in a well-ventilated place. Keep cool.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Methyl methacrylate	80-62-6	50 - <100%
2-Propenoic acid, 2-ethylhexyl ester	103-11-7	10 - <20%
1,4-Butanediol Dimethyacrylate	2082-81-7	1 - <5%
Dihydroxypropyl para-toluidine	38668-48-3	1 - <5%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTRE/doctor/ if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: Take off immediately all contaminated clothing. Get medical attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Do not taste or swallow. Wash hands thoroughly after handling. Avoid contact with eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 410 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl methacrylate	TWA	50 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Methyl methacrylate	TWA	50 ppm 205 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof ventilation equipment.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Do not eat, drink or smoke when using the product. Wash hands after handling. Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: liquid
Color: Violet
Odor: Mild petroleum/solvent
Odor threshold: No data available.
pH: No data available.
Melting point/freezing point: -48 °C -54 °F
Initial boiling point and boiling range: 100.3 °C 212.5 °F
Flash Point: 11.5 °C 52.7 °F
Evaporation rate: Slower than Ether
Flammability (solid, gas): No
Upper/lower limit on flammability or explosive limits
Flammability limit - upper (%): 12.5 %(V)

Flammability limit - lower (%):	2.1 %(V)
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	0.99
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Causes skin irritation. May cause an allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral
Product: ATEmix: 331.84 mg/kg

Dermal
Product: ATEmix: 59,999.74 mg/kg

Inhalation
Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Methyl methacrylate	LC 50 (Rat): 29.8 mg/l

Repeated dose toxicity
Product: No data available.

Skin Corrosion/Irritation
Product: No data available.

Specified substance(s):

Methyl methacrylate	in vivo (Rabbit): irritating after 4/24h occluded exposure Experimental result, Weight of Evidence study
2-Propenoic acid, 2-ethylhexyl ester	in vivo (Rabbit): Irritating Experimental result, Key study

Serious Eye Damage/Eye Irritation
Product: No data available.
Specified substance(s):

2-Propenoic acid, 2-ethylhexyl ester	Rabbit, 24 - 48 hrs: Not irritating

Respiratory or Skin Sensitization
Product: No data available.

Carcinogenicity
Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:
No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:
No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):
No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):
Methyl methacrylate — LC 50 (Fathead minnow (Pimephales promelas), 96 h): 130 mg/l Mortality

Aquatic Invertebrates
Product: No data available.

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Specified substance(s):
Methyl methacrylate Log Kow: 1.38

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1866, RESIN SOLUTION, 3, PG II

CFR / DOT:

UN1866, Resin solution, 3, PG II

IMDG:

UN1866, RESIN SOLUTION, 3, PG II

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Methyl methacrylate	10000 lbs
2-Propenoic acid, 2-ethylhexyl ester	10000 lbs
1,4-Butanediol Dimethyacrylate	10000 lbs
Dihydroxypropyl para-toluidine	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Methyl methacrylate

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

No ingredient regulated by CA Prop 65 present.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester

US. Massachusetts RTK - Substance List

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester

US. Rhode Island RTK

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester

International regulations

Montreal protocol

not applicable

Stockholm convention

not applicable

Rotterdam convention

not applicable

Kyoto protocol

not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	0 g/l
VOC Method 310	:	0.00 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	05/25/2017
Version #:	1.0
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: Tremco PUMA TC Gray - 6 GAL
Material: 470718 805

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 2

Health Hazards

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Skin sensitizer	Category 1

Unknown toxicity - Health

Acute toxicity, oral	26.3 %
Acute toxicity, dermal	36.2 %
Acute toxicity, inhalation, vapor	67.8 %
Acute toxicity, inhalation, dust or mist	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Highly flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace.

Response: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse. In case of fire: Use … to extinguish.

Storage: Store in well-ventilated place. Keep cool.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Methyl methacrylate	80-62-6	30 - 60%
2-Propenoic acid, 2-ethylhexyl ester	103-11-7	15 - 40%
Barium sulfate	7727-43-7	7 - 13%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTRE/doctor/ if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact:	Take off immediately all contaminated clothing. Get medical attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms:	Respiratory tract irritation. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.

Indication of immediate medical attention and special treatment needed

Treatment:	Get medical attention if symptoms occur.

5. Fire-fighting measures

General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 410 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (02 2014)
Barium sulfate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Barium sulfate - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Barium sulfate - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)

Chemical name	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl methacrylate	TWA	50 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methyl methacrylate	TWA	50 ppm 205 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Barium sulfate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Barium sulfate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Barium sulfate	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Barium sulfate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Barium sulfate - Respirable dust.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof ventilation equipment.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures:	Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Gray
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	100.3 °C 212.5 °F
Flash Point:	11.5 °C 52.7 °F(Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	12.5 %(V)
Flammability limit - lower (%):	2.1 %(V)
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.1
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.

Incompatible Materials:	Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Causes skin irritation. May cause an allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral
Product: ATEmix: 15,790.31 mg/kg

Dermal
Product: ATEmix: 11,706.42 mg/kg

Inhalation
Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Methyl methacrylate	LC 50 (Rat): 29.8 mg/l

Repeated dose toxicity
Product: No data available.

Skin Corrosion/Irritation
Product: No data available.

Specified substance(s):

Methyl methacrylate	in vivo (Rabbit): irritating after 4/24h occluded exposure Experimental result, Weight of Evidence study
2-Propenoic acid, 2-ethylhexyl ester	in vivo (Rabbit): Irritating Experimental result, Key study
Barium sulfate	validated "in vitro" test method Not irritant Read-across from supporting substance (structural analogue or surrogate), Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

2-Propenoic acid, 2-ethylhexyl ester	Rabbit, 24 - 48 hrs: Not irritating
Barium sulfate	Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):
Methyl methacrylate — LC 50 (Fathead minnow (Pimephales promelas), 96 h): 130 mg/l Mortality

Aquatic Invertebrates
Product: No data available.

Specified substance(s):
Barium sulfate — EC 50 (Tubificid worm (Tubifex tubifex), 24 h): 34.2 - 57.71 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):
Barium sulfate — LC 1 (Oncorhynchus mykiss, 28 d): 2,813 µg/l Experimental result, Supporting study
LC 50 (Oncorhynchus mykiss, 28 d): 42,700 µg/l Experimental result, Supporting study
LC 10 (Oncorhynchus mykiss, 28 d): 9,543 µg/l Experimental result, Supporting study

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Specified substance(s):
Methyl methacrylate Log Kow: 1.38

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1866, RESIN SOLUTION, 3, PG II

CFR / DOT:

UN1866, Resin solution, 3, PG II

IMDG:

UN1866, RESIN SOLUTION, 3, PG II

Further Information:
The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.
Barium sulfate	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.
Barium sulfate	1000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Methyl methacrylate	10000 lbs
2-Propenoic acid, 2-ethylhexyl ester	10000 lbs
Barium sulfate	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Methyl methacrylate

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

No ingredient regulated by CA Prop 65 present.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester
Barium sulfate

US. Massachusetts RTK - Substance List

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester
Barium sulfate

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester
Barium sulfate

US. Rhode Island RTK

Chemical Identity
Methyl methacrylate

International regulations

Montreal protocol
not applicable

Stockholm convention
not applicable

Rotterdam convention
not applicable

Kyoto protocol
not applicable

VOC: When appropriately mixed with the other part, product has a VOC less water and exempt solvent of: 0 g/l

Regulatory VOC (less water and exempt solvent)	:	0 g/l 0 g/l
VOC Method 310	:	0.00 %

Inventory Status:

Australia AICS:	All components in this product are listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	All components in this product are listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	02/17/2017
Version #:	2.0
Further Information:	No data available.

Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: Tremco PUMA TC Slate Gray - 6 GAL
Material: 470831 805

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 1

Health Hazards

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Skin sensitizer	Category 1

Unknown toxicity - Health

Acute toxicity, oral	26.3 %
Acute toxicity, dermal	56.9 %
Acute toxicity, inhalation, vapor	67.8 %
Acute toxicity, inhalation, dust or mist	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Extremely flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace.

Response: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse. In case of fire: Use … to extinguish.

Storage: Store in well-ventilated place. Keep cool.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Methyl methacrylate	80-62-6	30 - 60%
2-Propenoic acid, 2-ethylhexyl ester	103-11-7	15 - 40%
Barium sulfate	7727-43-7	7 - 13%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTRE/doctor/ if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact:	Take off immediately all contaminated clothing. Get medical attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms:	Respiratory tract irritation. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.

Indication of immediate medical attention and special treatment needed

Treatment:	Get medical attention if symptoms occur.

5. Fire-fighting measures

General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 410 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (02 2014)
Barium sulfate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Barium sulfate - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Barium sulfate - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)

Chemical name	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl methacrylate	TWA	50 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methyl methacrylate	TWA	50 ppm 205 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Barium sulfate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Barium sulfate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Barium sulfate	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Barium sulfate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Barium sulfate - Respirable dust.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof ventilation equipment.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures:	Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Dark gray
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	11.5 °C 52.7 °F(Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	12.5 %(V)
Flammability limit - lower (%):	2.1 %(V)
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.1
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.

Incompatible Materials:	Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Causes skin irritation. May cause an allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Methyl methacrylate	LD 50 (Rat): 7,900 mg/kg
2-Propenoic acid, 2-ethylhexyl ester	LD 50 (Rat): 4,435 mg/kg
Barium sulfate	LD 50 (Rat): 364 g/kg

Dermal

Product:	ATEmix: 8,244.42 mg/kg

Inhalation

Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Methyl methacrylate	LC 50 (Rat): 29.8 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Methyl methacrylate	in vivo (Rabbit): irritating after 4/24h occluded exposure Experimental result, Weight of Evidence study
2-Propenoic acid, 2-ethylhexyl ester	in vivo (Rabbit): Irritating Experimental result, Key study
Barium sulfate	validated "in vitro" test method Not irritant Read-across from supporting substance (structural analogue or surrogate), Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

2-Propenoic acid, 2-ethylhexyl ester	Rabbit, 24 - 48 hrs: Not irritating
Barium sulfate	Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):
Methyl methacrylate — LC 50 (Fathead minnow (Pimephales promelas), 96 h): 130 mg/l Mortality

Aquatic Invertebrates
Product: No data available.

Specified substance(s):
Barium sulfate — EC 50 (Tubificid worm (Tubifex tubifex), 24 h): 34.2 - 57.71 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):
Barium sulfate — LC 1 (Oncorhynchus mykiss, 28 d): 2,813 µg/l Experimental result, Supporting study
LC 50 (Oncorhynchus mykiss, 28 d): 42,700 µg/l Experimental result, Supporting study
LC 10 (Oncorhynchus mykiss, 28 d): 9,543 µg/l Experimental result, Supporting study

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Specified substance(s):
Methyl methacrylate Log Kow: 1.38

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1866, RESIN SOLUTION, 3, PG II

CFR / DOT:

UN1866, Resin solution, 3, PG II

IMDG:

UN1866, RESIN SOLUTION, 3, PG II

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.
Barium sulfate	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.
Barium sulfate	1000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Methyl methacrylate	10000 lbs
2-Propenoic acid, 2-ethylhexyl ester	10000 lbs
Barium sulfate	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Methyl methacrylate

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

No ingredient regulated by CA Prop 65 present.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester
Barium sulfate

US. Massachusetts RTK - Substance List

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester
Barium sulfate

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester
Barium sulfate

US. Rhode Island RTK

Chemical Identity
Methyl methacrylate

International regulations

Montreal protocol
not applicable

Stockholm convention
not applicable

Rotterdam convention
not applicable

Kyoto protocol
not applicable

VOC: When appropriately mixed with the other part, product has a VOC less water and exempt solvent of:
0 g/l

Regulatory VOC (less water and exempt solvent)	:	0 g/l
VOC Method 310	:	0.00 %

Inventory Status:

Australia AICS:	All components in this product are listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	All components in this product are listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	02/17/2017
Version #:	2.0
Further Information:	No data available.

Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: Tremco PUMA TC Tintable - 6 GAL
Material: 470700 805

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 2

Health Hazards

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Skin sensitizer	Category 1

Unknown toxicity - Health

Acute toxicity, oral	28.7 %
Acute toxicity, dermal	51.3 %
Acute toxicity, inhalation, vapor	65.1 %
Acute toxicity, inhalation, dust or mist	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement:	Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace.
Response:	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse. In case of fire: Use … to extinguish.
Storage:	Store in well-ventilated place. Keep cool.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Methyl methacrylate	80-62-6	30 - 60%
2-Propenoic acid, 2-ethylhexyl ester	103-11-7	15 - 40%
Barium sulfate	7727-43-7	10 - 30%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTRE/doctor/ if you feel unwell. Rinse mouth.
Inhalation:	Move to fresh air.

Skin Contact:	Take off immediately all contaminated clothing. Get medical attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms:	Respiratory tract irritation. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.

Indication of immediate medical attention and special treatment needed

Treatment:	Get medical attention if symptoms occur.

5. Fire-fighting measures

General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 410 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (02 2014)
Barium sulfate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Barium sulfate - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Barium sulfate - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)

Chemical name	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl methacrylate	TWA	50 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methyl methacrylate	TWA	50 ppm 205 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Barium sulfate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Barium sulfate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Barium sulfate	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Barium sulfate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Barium sulfate - Respirable dust.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof ventilation equipment.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures:	Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Off-white
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	100.3 °C 212.5 °F
Flash Point:	11.5 °C 52.7 °F(Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	12.5 %(V)
Flammability limit - lower (%):	2.1 %(V)
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	38.7 mbar
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.1
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.

Incompatible Materials:	Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Causes skin irritation. May cause an allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Methyl methacrylate	LD 50 (Rat): 7,900 mg/kg
2-Propenoic acid, 2-ethylhexyl ester	LD 50 (Rat): 4,435 mg/kg
Barium sulfate	LD 50 (Rat): 364 g/kg

Dermal

Product:	ATEmix: 7,292.85 mg/kg

Inhalation

Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Methyl methacrylate	LC 50 (Rat): 29.8 mg/l

Repeated dose toxicity
Product: No data available.

Skin Corrosion/Irritation
Product: No data available.

Specified substance(s):

Methyl methacrylate	in vivo (Rabbit): irritating after 4/24h occluded exposure Experimental result, Weight of Evidence study
2-Propenoic acid, 2-ethylhexyl ester	in vivo (Rabbit): Irritating Experimental result, Key study
Barium sulfate	validated "in vitro" test method Not irritant Read-across from supporting substance (structural analogue or surrogate), Key study

Serious Eye Damage/Eye Irritation
Product: No data available.
Specified substance(s):

2-Propenoic acid, 2-ethylhexyl ester	Rabbit, 24 - 48 hrs: Not irritating
Barium sulfate	Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization
Product: No data available.

Carcinogenicity
Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:
No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:
No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):
No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):
Methyl methacrylate — LC 50 (Fathead minnow (Pimephales promelas), 96 h): 130 mg/l Mortality

Aquatic Invertebrates
Product: No data available.

Specified substance(s):
Barium sulfate — EC 50 (Tubificid worm (Tubifex tubifex), 24 h): 34.2 - 57.71 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):
Barium sulfate — LC 1 (Oncorhynchus mykiss, 28 d): 2,813 µg/l Experimental result, Supporting study
LC 50 (Oncorhynchus mykiss, 28 d): 42,700 µg/l Experimental result, Supporting study
LC 10 (Oncorhynchus mykiss, 28 d): 9,543 µg/l Experimental result, Supporting study

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Specified substance(s):
Methyl methacrylate Log Kow: 1.38

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1866, RESIN SOLUTION, 3, PG III

CFR / DOT:

UN1866, Resin solution, 3, PG III

IMDG:

UN1866, RESIN SOLUTION, 3, PG III

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.
Barium sulfate	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.
Barium sulfate	1000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Methyl methacrylate	10000 lbs
2-Propenoic acid, 2-ethylhexyl ester	10000 lbs
Barium sulfate	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Methyl methacrylate

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

No ingredient regulated by CA Prop 65 present.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester
Barium sulfate

US. Massachusetts RTK - Substance List

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester
Barium sulfate

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester
Barium sulfate

US. Rhode Island RTK

Chemical Identity
Methyl methacrylate

International regulations

Montreal protocol
not applicable

Stockholm convention
not applicable

Rotterdam convention
not applicable

Kyoto protocol
not applicable

VOC: When appropriately mixed with the other part, product has a VOC less water and exempt solvent of:
0 g/l

Regulatory VOC (less water and exempt solvent)	:	0 g/l
VOC Method 310	:	0.00 %

Inventory Status:

Australia AICS:	All components in this product are listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	All components in this product are listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	02/17/2017
Version #:	2.0
Further Information:	No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

SAFETY DATA SHEET

1. Identification

Material name: Tremco PUMA WC - 6 GAL
Material: 470570 805

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 1

Health Hazards

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Skin sensitizer	Category 1

Unknown toxicity - Health

Acute toxicity, oral	30.6 %
Acute toxicity, dermal	40.6 %
Acute toxicity, inhalation, vapor	51.6 %
Acute toxicity, inhalation, dust or mist	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement:	Extremely flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace.
Response:	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse. In case of fire: Use … to extinguish.
Storage:	Store in well-ventilated place. Keep cool.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Methyl methacrylate	80-62-6	40 - 70%
2-Propenoic acid, 2-ethylhexyl ester	103-11-7	10 - 30%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTRE/doctor/ if you feel unwell. Rinse mouth.
Inhalation:	Move to fresh air.

Skin Contact:	Take off immediately all contaminated clothing. Get medical attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms:	Respiratory tract irritation. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.

Indication of immediate medical attention and special treatment needed

Treatment:	Get medical attention if symptoms occur.

5. Fire-fighting measures

General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 410 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl methacrylate	TWA	50 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methyl methacrylate	TWA	50 ppm 205 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:	Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof ventilation equipment.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Milky white
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	11.5 °C 52.7 °F(Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	12.5 %(V)
Flammability limit - lower (%):	2.5 %(V)
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	0.99

Solubility(ies)

Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Causes skin irritation. May cause an allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Methyl methacrylate	LD 50 (Rat): 7,900 mg/kg
2-Propenoic acid, 2-ethylhexyl ester	LD 50 (Rat): 4,435 mg/kg

Dermal

Product: ATEmix: 213,840 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Methyl methacrylate	LC 50 (Rat): 29.8 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Methyl methacrylate	in vivo (Rabbit): irritating after 4/24h occluded exposure Experimental result, Weight of Evidence study
2-Propenoic acid, 2-ethylhexyl ester	in vivo (Rabbit): Irritating Experimental result, Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

2-Propenoic acid, 2-ethylhexyl ester	Rabbit, 24 - 48 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):
No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Specified substance(s):
Methyl methacrylate LC 50 (Fathead minnow (Pimephales promelas), 96 h): 130 mg/l Mortality

Aquatic Invertebrates
Product: No data available.

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability

Biodegradation
Product: No data available.

BOD/COD Ratio
Product: No data available.

Bioaccumulative potential
Bioconcentration Factor (BCF)
Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product: No data available.

Specified substance(s):
Methyl methacrylate Log Kow: 1.38

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1866, RESIN SOLUTION, 3, PG II

CFR / DOT:

UN1866, Resin solution, 3, PG II

IMDG:

UN1866, RESIN SOLUTION, 3, PG II

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Methyl methacrylate	10000 lbs
2-Propenoic acid, 2-ethylhexyl ester	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Methyl methacrylate

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

No ingredient regulated by CA Prop 65 present.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester

US. Massachusetts RTK - Substance List

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Methyl methacrylate
2-Propenoic acid, 2-ethylhexyl ester

US. Rhode Island RTK

Chemical Identity
Methyl methacrylate

International regulations

Montreal protocol
not applicable

Stockholm convention
not applicable

Rotterdam convention
not applicable

Kyoto protocol
not applicable

VOC: When appropriately mixed with the other part, product has a VOC less water and exempt solvent of:
0 g/l

Regulatory VOC (less water and exempt solvent)	:	0 g/l
VOC Method 310	:	0.00 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	02/17/2017
Version #:	2.0
Further Information:	No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.